



Akzonobel Industrial Coatings Korea

# MATERIAL SAFETY DATA SHEET

## RESOTHANE-HT#500 RJ5

Date of issue: 2013-06-26

Revision date: Not applicable

Version: R0001.0001

### 1. IDENTIFICATION

#### A. Product name

- RESOTHANE-HT#500 RJ5 [KF000032244]

#### B. Recommended use and restriction on use

- General use : paint applid on plastic resin
- Restriction on use : Do not use for other purposes

#### C. Manufacturer / Supplier / Distributor information

##### ○ Manufacturer information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 60, Bonsan 1-ro 56beon-gil, Jinyeong-eup, Gimhae-si, Gyeongsangnam-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 55-720-0200
- Fax number :
- E-mail address :

##### ○ Supplier/Distributor information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 11, Byeolmang-ro 459beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 31-490-4200
- Fax number :
- E-mail address :

### 2. HAZARD IDENTIFICATION

#### A. GHS Classification

- Acute toxicity (inhalation: vapor) : Category4
- Chronic aquatic toxicity : Category3
- Carcinogenicity : Category1B
- Reproductive toxicity : Category1A
- Germ cell mutagenicity : Category1B
- Serious eye damage/irritation : Category2
- Flammable liquids : Category2
- Specific target organ toxicity(Single exposure) : Category2
- Specific target organ toxicity(Repeated exposure) : Category2
- Skin corrosion/irritation : Category2

#### B. GHS label elements

##### ○ Hazard symbols



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



○ **Signal words**

- Danger

○ **Hazard statements**

- H225 Highly flammable liquid and vapour
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H340 May cause genetic defects
- H350 May cause cancer
- H360 May damage fertility or the unborn child
- H371 May cause damage to organs (Refer Section SDS 11)
- H373 May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)
- H412 Harmful to aquatic life with long lasting effects

○ **Precautionary statements**

**1) Prevention**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

**2) Response**

- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P309+P311 If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).

**3) Storage**

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

**4) Disposal**



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

### C. Other hazards which do not result in classification : (NFPA Classification)

#### o NFPA grade (0 ~ 4 level)

- Health : 2, Flammability : 0, Reactivity : 0

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
2-Methyl-2-propenoic acid butyl ester polymer with 2-hydroxyethyl 2-methyl-2-propenoate and methyl 2-methyl-2-propenoate	-	31942-54-8	10 ~ 20
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	10 ~ 20
4-Methyl-2-pentanone	Methylisobutyl ketone, MIBK	108-10-1	10 ~ 20
Xylene	Dimethylbenzene	1330-20-7	1 ~ 10
Ethyleneglycol monoethyl ether acetate	2-Ethoxyethyl acetate	111-15-9	1 ~ 10
Methyl Ethyl Ketone	2-Butanone	78-93-3	1 ~ 10
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	1 ~ 10
Toluene	Methylbenzene	108-88-3	1 ~ 10
2-Methyl-2-Propenoic acid, polymer with 2-ethylhexyl 2-propenoate, 2-hydroxyethyl 2-methyl-2-propenoate and methyl 2-methyl-2-propenoate	-	61579-38-2	1 ~ 10
Ethylbenzene	Benzene, ethyl-	100-41-4	1 ~ 10
Cellulose acetate butylate	Cellulose, acetate butanoate	9004-36-8	1 ~ 10
Aluminium	Allbri aluminum paste and powder	7429-90-5	1 ~ 10
Stoddard solvent	Turpentine, mineral	8052-41-3	1 ~ 10
Fluorophlogopite	-	12003-38-2	1 ~ 10
Naphtha (petroleum), hydrotreated heavy	Naphtha	64742-48-9	0 ~ 1
Ethanol	Alcohol anhydrous	64-17-5	0 ~ 1
Secret	Secret	-	1 ~ 10

### 4. FIRST AID MEASURES

#### A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contact lenses if worn.

#### B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

#### C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

#### **D. Ingestion contact**

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

#### **E. Delayed and immediate effects and also chronic effects from short and long term exposure**

- Not available

#### **F. Notes to physician**

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

### **5. FIREFIGHTING MEASURES**

#### **A. Suitable (Unsuitable) extinguishing media**

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

#### **B. Specific hazards arising from the chemical**

- Not available

#### **C. Special protective actions for firefighters**

- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- Avoid inhalation of materials or combustion by-products.
- Do not access if the tank on fire.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

### **6. ACCIDENTAL RELEASE MEASURES**

#### **A. Personal precautions, protective equipment and emergency procedures**

- Wear proper personal protective apparatus as indicated in Section 8 and avoid skin contact and inhalation.
- Must work against the wind, let the upwind people to evacuate.
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

#### **B. Environmental precautions**

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

#### **C. Methods and materials for containment and cleaning up**

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.
- Spilled material should be treated as a potential risk of waste collected.

## 7. HANDLING AND STORAGE

### A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Get the manual before use.
- Operators should wear antistatic footwear and clothing.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

### B. Conditions for safe storage, including any incompatibilities

- Save applicable laws and regulations.
- Do not apply any physical shock to container.
- Avoid direct sunlight.
- Keep sealed when not in use.
- No open fire.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### A. Exposure limits

- o ACGIH TLV
  - [Isobutyl acetate] : TWA 150 ppm
  - [4-Methyl-2-pentanone] : TWA 50 ppm
  - [Xylene] : TWA 100 ppm
  - [Ethyleneglycol monoethyl ether acetate] : TWA 5 ppm
  - [Methyl Ethyl Ketone] : TWA 200 ppm
  - [n-Butyl acetate] : TWA 150 ppm
  - [Toluene] : TWA 50 ppm
  - [Ethylbenzene] : TWA 100 ppm
  - [Aluminium] : TWA : 10 mg/m3 Aluminium(metal dust)
  - [Stoddard solvent] : TWA 100 ppm
  - [Secret] : TWA 400 ppm
  - [Secret] : TWA 3.5 mg/m3
  - [Secret] : TWA 20 ppm
  - [Secret] : TWA : 5 mg/m3 (fume)
  - [Ethanol] : TWA 1000 ppm
  - [Secret] : TWA 200 ppm

### B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

### C. Personal protective equipment

#### ○ Respiratory protection

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

#### ○ Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

#### ○ Hand protection

- Wear appropriate chemical resistant glove.

#### ○ Skin protection

- Wear appropriate chemical resistant protective clothing.

#### ○ Others

- Not available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(Viscous liquid)
- Color	Metalic Gray
B. Odor	Not available
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	100 °C
G. Flash point	21 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity	0.91 ~ 0.97
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	Not available

## 10. STABILITY AND REACTIVITY

### A. Chemical stability

- This material is stable under recommended storage and handling conditions.

### B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

**C. Conditions to avoid**

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

**D. Incompatible materials**

- Not available

**E. Hazardous decomposition products**

- May emit flammable vapour if involved in fire.

**11. TOXICOLOGICAL INFORMATION****A. Information on the likely routes of exposure**

- (Respiratory tracts)
  - Not available
- (Oral)
  - Not available
- (Eye/Skin)
  - Causes serious eye irritation
  - Causes skin irritation

**B. Delayed and immediate effects and also chronic effects from short and long term exposure**

- Acute toxicity
  - \* Oral
    - [Isobutyl acetate] : LD50 = 15400 mg/kg Rat
    - [4-Methyl-2-pentanone] : LD50 = 2080 mg/kg Rat
    - [Xylene] : LD50 3500 mg/kg Rat
    - [Ethylene glycol monoethyl ether acetate] : LD50 = 2700 mg/kg Rat
    - [Methyl Ethyl Ketone] : LD50 2737 mg/kg Rat
    - [n-Butyl acetate] : LD50 = 14130 mg/kg Rat
    - [Toluene] : LD50 2600 mg/kg Rat
    - [Ethylbenzene] : LD50 = 3500 mg/kg Rat
    - [Stoddard solvent] : LD50 > 5000 mg/kg Rat
    - [Secret] : LD50 5620 mg/kg Rat
    - [Secret] : LD50 = 3672 mg/kg Rat
    - [Secret] : LD50 = 15400 mg/kg Rat
    - [Secret] : LD50 = 3300 mg/kg (Species : not available)
    - [Secret] : LD50 > 5000 mg/kg Rat
    - [Secret] : LD50 = 790 mg/kg Rat
    - [Secret] : LD50 > 10000 mg/kg Rat
    - [Secret] : LD50 = 8532 mg/kg Rat
    - [Naphtha (petroleum), hydrotreated heavy] : LD50 > 15000 mg/kg Rat
    - [Ethanol] : LD50 = 6200 mg/kg Rat
    - [Secret] : LD50 = 5000 mg/kg Rat
    - [Secret] : LD50 = 4710mg/kg Rat
    - [Secret] : LD50 = 2369 mg/kg Rat
    - [Secret] : LD50 = 8400 mg/kg Rat
    - [Secret] : LD50 = 7725 mg/kg Rat (Oral)
    - [Secret] : LD50 > 15000 mg/kg
    - [Secret] : LD50 = 600 mg/kg Rat
    - [Secret] : LD50 > 3000 mg/kg Rat
    - [Secret] : LD50 6200 mg/kg Rat



- [Secret] : LD50 = 526 mg/kg Rat

**\* Dermal**

- [Isobutyl acetate] : LD50 = 17400 mg/kg rabbit
- [4-Methyl-2-pentanone] : LD50 = 3000 mg/kg rabbit
- [Xylene] : LD50 4350 mg/kg Rabbit
- [Methyl Ethyl Ketone] : LD50 6480 mg/kg rabbit
- [n-Butyl acetate] : LD50 = 17600 mg/kg Rabbit
- [Toluene] : LD50 120000 mg/kg Rat
- [Ethylbenzene] : LD50 = 15400 mg/kg Rabbit
- [Secret] : LD50 > 18000 mg/kg Rabbit
- [Secret] : LD50 > 2000 mg/kg Rat
- [Secret] : LD50 = 3000 mg/kg rabbit
- [Secret] : LD50 = 5000 mg/kg
- [Secret] : LD50 > 2000 mg/kg Rabbit
- [Secret] : LD50 = 3402 mg/kg rabbit
- [Secret] : LD50 > 5000 mg/kg Rabbit
- [Naphtha (petroleum), hydrotreated heavy] : LD50 > 3160 mg/kg Rabbit
- [Secret] : LD50 = 12870 mg/kg rabbit
- [Secret] : LD50 = 5000 mg/kg Rat
- [Secret] : LD50 15800 mg/kg rabbit
- [Secret] : LD50 = 1488 mg/kg rabbit

**\* Inhalation**

- [Isobutyl acetate] : LC50 = 8000 ppm 4 hr Rat
- [4-Methyl-2-pentanone] : LC50 = 8.2 mg/l Rat
- [Xylene] : Steam LC50 6700 ppm 4 hr Rat (Equivalents : 29.09 mg/L)
- [Ethyleneglycol monoethyl ether acetate] : LC50 = 12.1 mg/l Rat (8hr)
- [Methyl Ethyl Ketone] : Steam LC50 32 mg/l 4 hr Mouse
- [n-Butyl acetate] : Steam LC50 = 2000 ppm Rat
- [Toluene] : LC50 12.5 mg/l 4 hr Rat
- [Ethylbenzene] : Steam LC50 = 4000 ppm 4 hr Rat (Equivalents : 17.4 mg/L)
- [Secret] : Steam LC50 100 mg/l 4 hr Rat (LC50 = 200 mg/L/1hr conversion  $\frac{2}{3}$ )
- [Secret] : dust LC50 > 4.83 mg/l Rat
- [Secret] : Steam LC50 > 2.0 mg/l Rat
- [Secret] : Mist LC50 > 5.28 mg/l 4 hr Rat
- [Secret] : Steam LC50 = 8000 ppm 4 hr Rat
- [Secret] : dust LC50  $\geq$  0.477 mg/kg 4 hr Rat
- [Secret] : Steam LC50 = 4345 ppm 6 hr Rat
- [Ethanol] : LC50 = 20000 ppm 10 hr Rat
- [Secret] : LC50 = 72600 mg/l 4 hr Rat
- [Secret] : Mist LC50 = 3400 ppm 4 hr Rat
- [Secret] : LC50 64000 ppm 4 hr Rat
- [Secret] : Steam LC50 8050 ppm 4 hr Rat

o **Skin corrosion/irritation**

- Causes skin irritation

o **Serious eye damage/irritation**

- Causes serious eye irritation

o **Respiratory sensitization**

- Not available

o **Skin sensitization**

- Not available

o **Carcinogenicity**

**\* IARC**

- [4-Methyl-2-pentanone] : 2B



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



- [Ethylbenzene] : Group 2B
- [Secret] : Group 2B (Cobalt and cobalt compounds)
- [Secret] : 2B
- [Secret] : Group 3 (Silica, amorphous)
- [Secret] : Group 3
- [Ethanol] : 1
- [Secret] : 3

**\* OSHA**

- Not available

**\* ACGIH**

- [4-Methyl-2-pentanone] : A3
- [Ethylbenzene] : A3
- [Aluminium] : A4
- [Fluorophlogopite] : A4 (Fluorides)
- [Secret] : A3 (Cobalt inorganic compounds)
- [Secret] : A4
- [Ethanol] : A3

**\* NTP**

- Not available

**\* EU CLP**

- [Stoddard solvent] : Carc. 1B
- [Naphtha (petroleum), hydrotreated heavy] : Carc. 1B
- [Secret] : Carc. 1B

○ **Germ cell mutagenicity**

- May cause genetic defects

○ **Reproductive toxicity**

- May damage fertility or the unborn child

○ **STOT-single exposure**

- May cause damage to organs (Refer Section SDS 11)

○ **STOT-repeated exposure**

- May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)

○ **Aspiration hazard**

- Not available

## 12. ECOLOGICAL INFORMATION

### A. Ecotoxicity

○ **Fish**

- [Isobutyl acetate] : LC50 = 17 mg/ℓ 96 hr
- [4-Methyl-2-pentanone] : LC50 = 540 mg/ℓ 96 hr
- [Xylene] : LC50 3.3 mg/ℓ 96 hr
- [Ethleneglycol monoethyl ether acetate] : LC50 = 40 mg/ℓ 96 hr
- [Methyl Ethyl Ketone] : LC50 3220 mg/ℓ 96 hr Pimephales promelas
- [n-Butyl acetate] : LC50 = 62 mg/ℓ 96 hr
- [Toluene] : LC50 24 mg/ℓ 96 hr Oncorhynchus mykiss
- [Ethylbenzene] : LC50 = 9.09 mg/ℓ 96 hr
- [Secret] : LC50 230 mg/ℓ 96 hr Pimephales promelas
- [Secret] : LC50 > 136 mg/ℓ 96 hr Brachydanio rerio
- [Secret] : LC50 = 800 mg/ℓ 96 hr Salmo gairdneri
- [Secret] : LC50 > 100 mg/ℓ 96 hr
- [Secret] : LC50 ≥ 100 mg/ℓ 96 hr Oryzias latipes
- [Naphtha (petroleum), hydrotreated heavy] : LC50 = 2200 mg/ℓ 96 hr Pimephales promelas
- [Ethanol] : LC50 = 42 mg/ℓ 96 hr Oncorhynchus mykiss



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Secret] : LC50 = 0.97 mg/ℓ 96 hr *Lepomis macrochirus*
- [Secret] : LC50 = 9.22 mg/ℓ 96 hr *Oncorhynchus mykiss*
- [Secret] : LC50 = 832 mg/ℓ 96 hr
- [Secret] : LC50 = 205 mg/ℓ 96 hr *Pimephales promelas*
- [Secret] : LC50 > 20000 mg/ℓ 96 hr *Oncorhynchus mykiss*
- [Secret] : LC50 15400 mg/ℓ 96 hr *Lepomis macrochirus*
- [Secret] : LC50 = 0.996 mg/ℓ 96 hr
- [Secret] : LC50 = 315 mg/ℓ 96 hr *Fundulus heteroclitus*
- [Secret] : LC50 4.8 mg/ℓ 96 hr *Brachydanio rerio*
- [Secret] : LC50 = 123.852 mg/ℓ 96 hr

#### ○ Crustaceans

- [4-Methyl-2-pentanone] : EC50 = 170 mg/ℓ 48 hr
- [Xylene] : LC50 190 mg/ℓ 96 hr
- [Methyl Ethyl Ketone] : EC50 5091 mg/ℓ 48 hr *Daphnia magna*
- [n-Butyl acetate] : LC50 = 32 mg/ℓ 48 hr
- [Toluene] : EC50 11.5 mg/ℓ 48 hr *Daphnia magna*
- [Ethylbenzene] : LC50 = 0.4 mg/ℓ 96 hr
- [Stoddard solvent] : LC50 = 0.4 ~ 2.3 mg/ℓ 48 hr
- [Secret] : EC50 717 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : LC50 > 136 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : EC50 = 5600 mg/ℓ 24 hr
- [Secret] : EC50 > 100 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : EC50 = 1983 mg/ℓ 48 hr
- [Secret] : EC50 = 373 mg/ℓ 48 hr *Daphnia magna*
- [Naphtha (petroleum), hydrotreated heavy] : LC50 = 2.6 mg/ℓ 96 hr (Species: *Chaetogammarus marinus*)
- [Ethanol] : EC50 = 2 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : EC50 = 20 mg/ℓ 24 hr
- [Secret] : EC50 = 6.14 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : LC50 = 1.23 mg/ℓ 48 hr
- [Secret] : LC50 > 2.8 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : EC50 = 32 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : LD50 > 100 mg/ℓ 96 hr *Daphnia magna*
- [Secret] : LC50 = 0.110 mg/ℓ 48 hr
- [Secret] : EC50 = 1.2 mg/ℓ 64 hr *Daphnia magna*
- [Secret] : EC50 ≥ 3.2 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : LC50 = 2332.935 mg/ℓ 48 hr

#### ○ Algae

- [Methyl Ethyl Ketone] : EC50 > 500 mg/ℓ 96 hr *Skeletonema costatum*
- [Secret] : EC50 1800 ~ 3200 mg/ℓ 72 hr (*Selenastrum* sp.)
- [Secret] : EC50 = 88 mg/ℓ 72 hr *Selenastrum capricornutum*
- [Secret] : EC50 = 450 mg/ℓ 96 hr *Selenastrum capricornutum*
- [Secret] : EC50 = 28 mg/ℓ 48 hr
- [Secret] : EC50 ≥ 1000 mg/ℓ 72 hr *Selenastrum capricornutum*
- [Secret] : EC50 = 2.2 mg/ℓ 96 hr
- [Secret] : EC50 = 0.017 mg/ℓ 96 hr
- [Secret] : EC50 = 19 mg/ℓ 72 hr *Selenastrum capricornutum*
- [Secret] : EC50 > 500 mg/ℓ 72 hr
- [Secret] : EC50 = 1890.263 mg/ℓ 96 hr
- [Secret] : EC50 = 0.615 mg/ℓ 96 hr
- [Secret] : EC50 = 9.337 mg/ℓ 96 hr

## B. Persistence and degradability

### ○ Persistence



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Isobutyl acetate] : log Kow = 1.78
- [4-Methyl-2-pentanone] : log Kow = 1.38
- [Ethyleneglycol monoethyl ether acetate] : log Kow = 0.59
- [Methyl Ethyl Ketone] : log Kow 0.29
- [n-Butyl acetate] : log Kow = 1.78
- [Toluene] : log Kow 2.73
- [Stoddard solvent] : log Kow = 3.16 ~ 7.06
- [Secret] : (Not applicable)
- [Secret] : log Kow 0.73
- [Secret] : log Kow = 3.3 ~ 6 (Estimates)
- [Secret] : log Kow = 0.97 (Estimates)
- [Secret] : log Kow = 0.43
- [Naphtha (petroleum), hydrotreated heavy] : log Kow = 2.1 ~ 6 (Estimates)
- [Secret] : log Kow = 0.37 (at 25 °C)
- [Secret] : log Kow = 2.1 ~ 6 (Estimates)
- [Secret] : log Kow = -0.54
- [Secret] : log Kow = 7.73
- [Secret] : log Kow = 0.63
- [Secret] : log Kow -0.77
- [Secret] : log Kow = 5.14
- [Secret] : log Kow = -2.7
- [Secret] : log Kow 4.57
- [Secret] : log Kow = 0.52

#### ○ Degradability

- [Secret] : BOD5/COD 0.81
- [Ethanol] : BOD5/COD = 0.57
- [Secret] : BOD5/COD = 0.43
- [Secret] : BOD5/COD = 0.68
- [Secret] : BOD = 0.32

### C. Bioaccumulative potential

#### ○ Bioaccumulative potential

- [Secret] : BCF 30
- [Secret] : BCF = 1351
- [Secret] : BCF = 0.16
- [Secret] : BCF = 44,000
- [Secret] : BCF = 3.162
- [Secret] : BCF = 180.1

#### ○ Biodegradation

- [Xylene] : 39 (%)
- [Ethyleneglycol monoethyl ether acetate] : Biodegradability = 86.9 (%)
- [Methyl Ethyl Ketone] : 89 (%) 20 day
- [n-Butyl acetate] : Biodegradability = 98 (%)
- [Toluene] : 86 (%) 20 day
- [Stoddard solvent] : Biodegradability = 12 ~ 13 (%)
- [Secret] : 100 (%) 28 day
- [Secret] : Biodegradability = 9 (%) 28 day (Aerobic)
- [Secret] : Biodegradability > 60 (%) 28 day
- [Naphtha (petroleum), hydrotreated heavy] : Biodegradability = 10 (%) 28 day (Aerobic, Activated Sludge, Domestic wastewater, Does not decompose easily)
- [Ethanol] : Biodegradability = 75 (%) 20 day (Aerobic, Other, Easily decomposed)
- [Secret] : Biodegradability = 38 (%) 28 day
- [Secret] : Biodegradability = 73 (%) 28 day



- [Secret] : Biodegradability = 47 ~ 52 (%) 5 day
- [Secret] : 41 ~ 42 (%) 28 day

#### D. Mobility in soil

- [Xylene] : log Kow = 3.12 (measured) (ortho), 3.2 (measured) (meta), 3.15 (measurements) (p) (5)
- [Ethylbenzene] : log Kow = 3.15 (11)
- [Ethanol] : Koc = 1
- [Secret] : Koc = 1.838

#### E. Other adverse effects

- Not available

### 13. DISPOSAL CONSIDERATIONS

#### A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- High temperature incinerate
- After taking off organic solvents that are supposed to be recycled, incinerate the rest of them at a high degree.

#### B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

### 14. TRANSPORT INFORMATION

#### A. UN number

- 1263

#### B. Proper shipping name

- Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

#### C. Hazard class

- 3

#### D. Packing group

- II

#### E. Marine pollutant

- [Ethylbenzene] : Applicable
- [Aluminium] : Applicable
- [Stoddard solvent] : Applicable
- [Secret] : Applicable

#### F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## 15. REGULATORY INFORMATION

### A. National and/or international regulatory information

#### ○ POPs Management Law

- Not applicable

#### ○ Information of EU Classification

##### \* Classification

- [Isobutyl acetate] : F; R11 R66
- [4-Methyl-2-pentanone] : F; R11 Xn; R20 Xi; R36/37 R66
- [Xylene] : R10 Xn; R20/21 Xi; R38
- [Ethyleneglycol monoethyl ether acetate] : R10 Repr. Cat. 2; R60-61 Xn; R20/21/22
- [Methyl Ethyl Ketone] : F; R11 Xi; R36 R66 R67
- [n-Butyl acetate] : R10 R66 R67
- [Toluene] : F; R11 Repr.Cat.3; R63 Xn; R48/20-65 Xi; R38 R67
- [Ethylbenzene] : F; R11Xn; R20
- [Aluminium] : F; R15-17
- [Stoddard solvent] : Carc. Cat. 2; R45 Muta. Cat. 2; R46 Xn; R65
- [Secret] : F; R11 Xi; R36 R66 R67
- [Secret] : Xn; R65
- [Secret] : R10 Xn; R 22 Xi; R37/38-41 R67
- [Secret] : R10
- [Naphtha (petroleum), hydrotreated heavy] : Carc. Cat. 2; R45/Muta. Cat. 2; R46, Xn; R65
- [Ethanol] : F; R11
- [Secret] : F; R11 Xi; R36 R67
- [Secret] : Carc. Cat. 2; R45/Muta. Cat. 2; R46, Xn; R65
- [Secret] : Repr. Cat. 2; R61, Xi; R36/37/38
- [Secret] : F; R11 T; R23/24/25-39/23/24/25
- [Secret] : R10 Repr. Cat. 2; R61 Xi; R37

##### \* Risk Phrases

- [Isobutyl acetate] : R11, R66
- [4-Methyl-2-pentanone] : R11, R20, R36/37, R66
- [Xylene] : R10, R20/21, R38
- [Ethyleneglycol monoethyl ether acetate] : R60, R61, R10, R20/21/22
- [Methyl Ethyl Ketone] : R11, R36, R66, R67
- [n-Butyl acetate] : R10, R66, R67
- [Toluene] : R11, R38, R48/20, R63, R65, R67
- [Ethylbenzene] : R11, R20
- [Aluminium] : R15, R17
- [Stoddard solvent] : R45, R46, R65
- [Secret] : R11, R36, R66, R67
- [Secret] : R65
- [Secret] : R10, R22, R37/38, R41, R67
- [Secret] : R10
- [Naphtha (petroleum), hydrotreated heavy] : R45, R65, R46
- [Ethanol] : R11
- [Secret] : R11, R36, R67
- [Secret] : R45, R65, R46
- [Secret] : R61, R36/37/38
- [Secret] : R11, R23/24/25, R39/23/24/25
- [Secret] : R61, R10, R37

##### \* Safety Phrase

- [Isobutyl acetate] : S2, S16, S23, S25, S29, S33
- [4-Methyl-2-pentanone] : S2, S9, S16, S29
- [Xylene] : S2, S25



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Ethyleneglycol monoethyl ether acetate] : S53, S45
- [Methyl Ethyl Ketone] : S2, S9, S16
- [n-Butyl acetate] : S2, S25
- [Toluene] : S2, S36/37, S46, S62
- [Ethylbenzene] : S2, S16, S24/25, S29
- [Aluminium] : S2, S7/8, S43
- [Stoddard solvent] : S53, S45
- [Secret] : S2, S16, S26, S33
- [Secret] : S2, S23, S24, S62
- [Secret] : S2, S7/9, S13, S26, S37/39, S46
- [Secret] : S2
- [Naphtha (petroleum), hydrotreated heavy] : S53, S45
- [Ethanol] : S2, S7, S16
- [Secret] : S2, S7, S16, S24/25, S26
- [Secret] : S53, S45
- [Secret] : S1/2, S7, S16, S36/37, S45
- **U.S. Federal regulations**
  - \* **OSHA PROCESS SAFETY (29CFR1910.119)**
    - Not applicable
  - \* **CERCLA Section 103 (40CFR302.4)**
    - [Isobutyl acetate] : 2267.995 kg 5000 lb
    - [4-Methyl-2-pentanone] : 2267.995 kg 5000 lb
    - [Xylene] : 45.3599 kg 100 lb
    - [Methyl Ethyl Ketone] : 2267.995 kg 5000 lb
    - [n-Butyl acetate] : 2267.995 kg 5000 lb
    - [Toluene] : 453.599 kg 1000 lb
    - [Ethylbenzene] : 453.599 kg 1000 lb
    - [Secret] : 2267.995 kg 5000 lb
  - \* **EPCRA Section 302 (40CFR355.30)**
    - Not applicable
  - \* **EPCRA Section 304 (40CFR355.40)**
    - Not applicable
  - \* **EPCRA Section 313 (40CFR372.65)**
    - [4-Methyl-2-pentanone] : Applicable
    - [Xylene] : Applicable
    - [Toluene] : Applicable
    - [Ethylbenzene] : Applicable
    - [Aluminium] : Applicable
    - [Secret] : Applicable
- **Rotterdam Convention listed ingredients**
  - Not applicable
- **Stockholm Convention listed ingredients**
  - Not applicable
- **Montreal Protocol listed ingredients**
  - Not applicable

## 16. OTHER INFORMATION

### A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

**B. Issue date**

- 2013-06-26

**C. Revision number and Last date revised**

- Not applicable

**D. Other**

- This MSDS is prepared according to the Globally Harmonized System (GHS).



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.