



Akzonobel Industrial Coatings Korea

MATERIAL SAFETY DATA SHEET

TX-F PRIMER PP BLACK

Date of issue: 2013-07-09

Revision date: 2014-03-11

Version: R0001.0003

1. IDENTIFICATION

A. Product name

- TX-F PRIMER PP BLACK

B. Recommended use and restriction on use

- General use : paint applid on plastic resin
- Restriction on use : Do not use for other purposes

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 60, Bonsan 1-ro 56beon-gil, Jinyeong-eup, Gimhae-si, Gyeongsangnam-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 55-720-0200
- Fax number :
- E-mail address :

○ Supplier/Distributor information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 11, Byeolmang-ro 459beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 31-490-4200
- Fax number :
- E-mail address :

2. HAZARD IDENTIFICATION

A. GHS Classification

- Acute toxicity (dermal) : Category4
- Acute toxicity (inhalation: vapor) : Category3
- Acute aquatic toxicity : Category1
- Carcinogenicity : Category1B
- Reproductive toxicity : Category1A
- Germ cell mutagenicity : Category1B
- Serious eye damage/irritation : Category2
- Flammable liquids : Category3
- Specific target organ toxicity(Single exposure) : Category1
- Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)
- Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)
- Skin corrosion/irritation : Category2



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Aspiration hazard : Category2

B. GHS label elements

○ Hazard symbols



○ Signal words

- Danger

○ Hazard statements

- H226 Flammable liquid and vapour
- H305 May be harmful if swallowed and enters airways
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H331 Toxic if inhaled
- H335 May cause respiratory irritation.
- H336 May cause drowsiness and dizziness.
- H340 May cause genetic defects
- H350 May cause cancer
- H360 May damage fertility or the unborn child
- H370 Causes damage to organs(Refer Section SDS 11)
- H400 Very toxic to aquatic life

○ Precautionary statements

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P307+P311 If exposed: Call a POISON CENTER or doctor/physician.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P311 Call a POISON CENTER or doctor/physician.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- P322 Specific measures
- P331 Do NOT induce vomiting.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).
- P391 Collect spillage.

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

o NFPA grade (0 ~ 4 level)

- Health : 2, Flammability : 3, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Cyclohexanone	Hexanon	108-94-1	20 ~ 30
Hexahydrobenzene	Cyclohexane	110-82-7	20 ~ 30
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	10 ~ 20
2,5-Furandione reaction products with polypropylene, chlorinated	-	68609-36-9	10 ~ 20
Talc	Talcum	14807-96-6	1 ~ 10
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	1 ~ 10
Propylene glycol methyl ether acetate	Propylene glycol monomethyl ether acetate	108-65-6	1 ~ 10
Solvent naphtha (petroleum), light arom.	Naphtha	64742-95-6	1 ~ 10
4-Methyl-2-pentanone	Methylisobutyl ketone, MIBK	108-10-1	1 ~ 10
Carbon black	Acetylene black	1333-86-4	1 ~ 10
Acetic acid ethyl ester	Ethyl acetate	141-78-6	1 ~ 10
Silicon dioxide	Silic anhydride	7631-86-9	1 ~ 10
Ethanol	Alcohol anhydrous	64-17-5	0 ~ 1
Secret	Secret	-	1 ~ 10

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contact lenses if worn.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Prevent the spread of the skin.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.
- Take the doctor's examination.

D. Ingestion contact

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Keep unauthorized personnel out.
- Avoid inhalation of materials or combustion by-products.
- Do not access if the tank on fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Ventilate closed spaces before entering.
- Remove all sources of ignition.
- Handling the damaged containers or spilled material after wearing protective equipment.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Avoid entering to sewers or water system.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.
- Spilled material should be treated as a potential risk of waste collected.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid direct physical contact.
- Get the manual before use.
- Refer to Engineering controls and personal protective equipment.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Check regularly for leaks.
- Do not apply direct heat.
- Save applicable laws and regulations.
- Avoid direct sunlight.
- No open fire.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- o ACGIH TLV
 - [Cyclohexanone] : TWA 20 ppm
 - [Hexahydrobenzene] : TWA 100 ppm
 - [n-Butyl acetate] : TWA 150 ppm
 - [Talc] : TWA : 3 mg/m3 Talc(respirable dust)
 - [Isobutyl acetate] : TWA 150 ppm
 - [4-Methyl-2-pentanone] : TWA 50 ppm
 - [Carbon black] : TWA 3.5 mg/m3
 - [Acetic acid ethyl ester] : TWA 400 ppm
 - [Ethanol] : TWA 1000 ppm
 - [Secret] : TWA 200 ppm



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Personal protective equipment

○ Respiratory protection

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

○ Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

○ Hand protection

- Wear appropriate chemical resistant glove.

○ Skin protection

- Wear appropriate chemical resistant protective clothing.

○ Others

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(Viscous liquid)
- Color	BLACK
B. Odor	Not available
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	79 °C
G. Flash point	23 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity	0.882~0.942
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	420 °C
Q. Decomposition temperature	Not available
R. Viscosity	43.6~49.6
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY

A. Chemical stability

- This material is stable under recommended storage and handling conditions.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION**A. Information on the likely routes of exposure**

- **(Respiratory tracts)**
 - May be harmful if swallowed and enters airways
 - May cause respiratory irritation.
- **(Oral)**
 - Not available
- **(Eye/Skin)**
 - Causes serious eye irritation
 - Causes skin irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- **Acute toxicity**
 - * **Oral**
 - [Hexahydrobenzene] : LD50 = 12705 mg/kg
 - [Cyclohexanone] : LD50 = 1800 mg/kg Rat
 - [n-Butyl acetate] : LD50 = 14130 mg/kg Rat
 - [Isobutyl acetate] : LD50 = 15400 mg/kg Rat
 - [Propylene glycol methyl ether acetate] : LD50 = 8532 mg/kg Rat
 - [Solvent naphtha (petroleum), light arom.] : LD50 = 8400 mg/kg Rat
 - [4-Methyl-2-pentanone] : LD50 = 2080 mg/kg Rat
 - [Carbon black] : LD50 = 15400 mg/kg Rat
 - [Acetic acid ethyl ester] : LD50 5620 mg/kg Rat
 - [Silicon dioxide] : LD50 = 3160 mg/kg Rat
 - [Ethanol] : LD50 = 6200 mg/kg Rat
 - [Secret] : LD50 = 1920 mg/kg Rat
 - [Secret] : LD50 > 5000 mg/kg Rat
 - [Secret] : LD50 = 4710mg/kg Rat
 - * **Dermal**
 - [Hexahydrobenzene] : LD50 > 2000 mg/kg Rabbit
 - [Cyclohexanone] : LD50 = 947 mg/kg Rabbit
 - [n-Butyl acetate] : LD50 = 17600 mg/kg Rabbit
 - [Isobutyl acetate] : LD50 = 17400 mg/kg rabbit
 - [Propylene glycol methyl ether acetate] : LD50 > 5000 mg/kg Rabbit
 - [Solvent naphtha (petroleum), light arom.] : LD50 > 2000 mg/kg Rabbit
 - [4-Methyl-2-pentanone] : LD50 = 3000 mg/kg rabbit
 - [Carbon black] : LD50 = 3000 mg/kg rabbit



- [Acetic acid ethyl ester] : LD50 > 18000 mg/kg Rabbit
- [Secret] : LD50 = 8500 mg/kg Rat
- [Secret] : LD50 > 5000 mg/kg Rabbit
- [Secret] : LD50 = 12870 mg/kg rabbit

*** Inhalation**

- [Cyclohexanone] : Steam LC50 = 2.375 mg/l Mouse
- [Hexahydrobenzene] : LC50 = 70 mg/l
- [n-Butyl acetate] : Steam LC50 = 2000 ppm Rat
- [Isobutyl acetate] : LC50 = 8000 ppm 4 hr Rat
- [Propylene glycol methyl ether acetate] : Steam LC50 = 4345 ppm 6 hr Rat
- [Solvent naphtha (petroleum), light arom.] : Mist LC50 = 3400 ppm 4 hr Rat
- [4-Methyl-2-pentanone] : LC50 = 8.2 mg/l Rat
- [Acetic acid ethyl ester] : Steam LC50 100 mg/l 4 hr Rat (LC50 = 200 mg/L/1hr conversion $\frac{1}{100}$)
- [Ethanol] : LC50 = 20000 ppm 10 hr Rat
- [Secret] : LC50 = 72600 mg/l 4 hr Rat

o **Skin corrosion/irritation**

- Causes skin irritation

o **Serious eye damage/irritation**

- Causes serious eye irritation

o **Respiratory sensitization**

- Not available

o **Skin sensitization**

- Not available

o **Carcinogenicity**

*** IARC**

- [Cyclohexanone] : 3
- [Talc] : 2B
- [4-Methyl-2-pentanone] : 2B
- [Carbon black] : 2B
- [Silicon dioxide] : 3
- [Ethanol] : 1
- [Secret] : 3

*** OSHA**

- Not available

*** ACGIH**

- [Cyclohexanone] : A3
- [4-Methyl-2-pentanone] : A3
- [Carbon black] : A4
- [Ethanol] : A3
- [Secret] : A4

*** NTP**

- Not available

*** EU CLP**

- [Solvent naphtha (petroleum), light arom.] : Carc. 1B

o **Germ cell mutagenicity**

- May cause genetic defects

o **Reproductive toxicity**

- May damage fertility or the unborn child

o **STOT-single exposure**

- Causes damage to organs(Refer Section SDS 11)
- May cause drowsiness and dizziness.
- May cause respiratory irritation.

o **STOT-repeated exposure**

- Not available



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

○ **Aspiration hazard**

- May be harmful if swallowed and enters airways

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

○ **Fish**

- [Cyclohexanone] : LC50 = 527 mg/ℓ 96 hr *Pimephales promelas*
- [n-Butyl acetate] : LC50 = 62 mg/ℓ 96 hr
- [Talc] : LC50 > 100000 mg/ℓ 24 hr *Brachydanio rerio*
- [Isobutyl acetate] : LC50 = 17 mg/ℓ 96 hr
- [Propylene glycol methyl ether acetate] : LC50 ≥ 100 mg/ℓ 96 hr *Oryzias latipes*
- [Solvent naphtha (petroleum), light arom.] : LC50 = 9.22 mg/ℓ 96 hr *Oncorhynchus mykiss*
- [4-Methyl-2-pentanone] : LC50 = 540 mg/ℓ 96 hr
- [Acetic acid ethyl ester] : LC50 230 mg/ℓ 96 hr *Pimephales promelas*
- [Ethanol] : LC50 = 42 mg/ℓ 96 hr *Oncorhynchus mykiss*
- [Secret] : LC50 = 13400 mg/ℓ 96 hr *Oncorhynchus mykiss*
- [Secret] : LC50 = 50 ~ 100 mg/ℓ 96 hr *Brachydanio rerio*
- [Secret] : LC50 = 87.095 mg/ℓ 96 hr
- [Secret] : LC50 > 100 mg/ℓ 96 hr
- [Secret] : LC50 = 123.852 mg/ℓ 96 hr

○ **Crustaceans**

- [Cyclohexanone] : EC50 = 820 mg/ℓ 24 hr *Daphnia magna*
- [Hexahydrobenzene] : EC50 = 0.9 mg/ℓ 48 hr
- [n-Butyl acetate] : LC50 = 32 mg/ℓ 48 hr
- [Talc] : LC50 = 94983.781 mg/ℓ 48 hr
- [Propylene glycol methyl ether acetate] : EC50 = 373 mg/ℓ 48 hr *Daphnia magna*
- [Solvent naphtha (petroleum), light arom.] : EC50 = 6.14 mg/ℓ 48 hr *Daphnia magna*
- [4-Methyl-2-pentanone] : EC50 = 170 mg/ℓ 48 hr
- [Carbon black] : EC50 = 5600 mg/ℓ 24 hr
- [Acetic acid ethyl ester] : EC50 717 mg/ℓ 48 hr *Daphnia magna*
- [Ethanol] : EC50 = 2 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : EC50 = 3940 ~ 4670 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : LC50 = 3317.276 mg/ℓ 48 hr
- [Secret] : LC50 = 2332.935 mg/ℓ 48 hr

○ **Algae**

- [Cyclohexanone] : EC50 = 32.9 mg/ℓ 72 hr (*Chlamydomonas reinhardtii* (Algae))
- [Talc] : LC50 = 48545.539 mg/ℓ
- [Propylene glycol methyl ether acetate] : EC50 ≥ 1000 mg/ℓ 72 hr *Selenastrum capricornutum*
- [Solvent naphtha (petroleum), light arom.] : EC50 = 19 mg/ℓ 72 hr *Selenastrum capricornutum*
- [Acetic acid ethyl ester] : EC50 1800 ~ 3200 mg/ℓ 72 hr (*Selenastrum* sp.)
- [Secret] : EC50 = 6.691 mg/ℓ 96 hr (No accurate information on Species)
- [Secret] : EC50 = 11.917 mg/ℓ 96 hr
- [Secret] : EC50 = 2.2 mg/ℓ 96 hr
- [Secret] : EC50 = 9.337 mg/ℓ 96 hr

B. Persistence and degradability

○ **Persistence**

- [Cyclohexanone] : log Kow = 0.81
- [n-Butyl acetate] : log Kow = 1.78
- [Talc] : log Kow = -1.50
- [Isobutyl acetate] : log Kow = 1.78
- [Propylene glycol methyl ether acetate] : log Kow = 0.43



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Solvent naphtha (petroleum), light arom.] : $\log K_{ow} = 2.1 \sim 6$ (Estimates)
- [4-Methyl-2-pentanone] : $\log K_{ow} = 1.38$
- [Acetic acid ethyl ester] : $\log K_{ow} = 0.73$
- [Silicon dioxide] : $\log K_{ow} = 0.53$
- [Secret] : $\log K_{ow} = 0.62$
- [Secret] : $\log K_{ow} = 1.03$
- [Secret] : $\log K_{ow} = 0.35$
- [Secret] : $\log K_{ow} = 0.52$

○ **Degradability**

- [Solvent naphtha (petroleum), light arom.] : $BOD_5/COD = 0.43$
- [Acetic acid ethyl ester] : $BOD_5/COD = 0.81$
- [Ethanol] : $BOD_5/COD = 0.57$

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [Cyclohexanone] : $BCF = 2.4$ (Estimates)
- [Hexahydrobenzene] : $BCF = 129$
- [Acetic acid ethyl ester] : $BCF = 30$
- [Silicon dioxide] : $BCF = 3.162$
- [Secret] : $BCF = 1.1$
- [Secret] : $BCF = 1.2$
- [Secret] : $BCF = 3.162$

○ **Biodegradation**

- [Hexahydrobenzene] : Biodegradability = 77 (%) 28 day
- [n-Butyl acetate] : Biodegradability = 98 (%)
- [Propylene glycol methyl ether acetate] : Biodegradability > 60 (%) 28 day
- [Acetic acid ethyl ester] : 100 (%) 28 day
- [Ethanol] : Biodegradability = 75 (%) 20 day (Aerobic, Other, Easily decomposed)
- [Secret] : Biodegradability = 98 (%) 28 day
- [Secret] : (More than 95% decomposed after 3 days)

D. Mobility in soil

- [Ethanol] : $K_{oc} = 1$
- [Secret] : $K_{oc} = 10.9$
- [Secret] : $K_{oc} = 1.838$

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designated waste is mixed, it is difficult to treat separately, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- High temperature incinerate
- After taking off organic solvents that are supposed to be recycled, incinerate the rest of them at a high degree.

B. Special precautions for disposal

- The user of this product must dispose by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

14. TRANSPORT INFORMATION

A. UN number

- 1263

B. Proper shipping name

- Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

C. Hazard class

- 3

D. Packing group

- III

E. Marine pollutant

- [Hexahydrobenzene] : Applicable
- [Solvent naphtha (petroleum), light arom.] : Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

o POPs Management Law

- Not applicable

o Information of EU Classification

* Classification

- [Hexahydrobenzene] : F; R11Xn; R65Xi; R38R67N; R50-53
- [Cyclohexanone] : R10Xn; R20
- [n-Butyl acetate] : R10 R66 R67
- [Isobutyl acetate] : F; R11 R66
- [Propylene glycol methyl ether acetate] : R10
- [Solvent naphtha (petroleum), light arom.] : Carc. Cat. 2; R45/Muta. Cat. 2; R46, Xn; R65
- [4-Methyl-2-pentanone] : F; R11 Xn; R20 Xi; R36/37 R66
- [Acetic acid ethyl ester] : F; R11 Xi; R36 R66 R67
- [Ethanol] : F; R11
- [Secret] : F; R11 Xi; R36 R67
- [Secret] : R10 Repr. Cat. 2; R61 Xi; R37

* Risk Phrases

- [Cyclohexanone] : R10, R20
- [Hexahydrobenzene] : R11, R38, R65, R67, R50/53
- [n-Butyl acetate] : R10, R66, R67
- [Isobutyl acetate] : R11, R66
- [Propylene glycol methyl ether acetate] : R10
- [Solvent naphtha (petroleum), light arom.] : R45, R65, R46
- [4-Methyl-2-pentanone] : R11, R20, R36/37, R66
- [Acetic acid ethyl ester] : R11, R36, R66, R67
- [Ethanol] : R11
- [Secret] : R11, R36, R67



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Secret] : R61, R10, R37

*** Safety Phrase**

- [Cyclohexanone] : S2, S25
- [Hexahydrobenzene] : S2, S9, S16, S25, S33, S51, S60, S61, S62
- [n-Butyl acetate] : S2, S25
- [Isobutyl acetate] : S2, S16, S23, S25, S29, S33
- [Propylene glycol methyl ether acetate] : S2
- [Solvent naphtha (petroleum), light arom.] : S53, S45
- [4-Methyl-2-pentanone] : S2, S9, S16, S29
- [Acetic acid ethyl ester] : S2, S16, S26, S33
- [Ethanol] : S2, S7, S16
- [Secret] : S2, S7, S16, S24/25, S26
- [Secret] : S53, S45

○ **U.S. Federal regulations**

*** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- [Cyclohexanone] : 2267.995 kg 5000 lb
- [Hexahydrobenzene] : 453.599 kg 1000 lb
- [n-Butyl acetate] : 2267.995 kg 5000 lb
- [Isobutyl acetate] : 2267.995 kg 5000 lb
- [4-Methyl-2-pentanone] : 2267.995 kg 5000 lb
- [Acetic acid ethyl ester] : 2267.995 kg 5000 lb

*** EPCRA Section 302 (40CFR355.30)**

- Not applicable

*** EPCRA Section 304 (40CFR355.40)**

- Not applicable

*** EPCRA Section 313 (40CFR372.65)**

- [Hexahydrobenzene] : Applicable
- [4-Methyl-2-pentanone] : Applicable
- [Secret] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2013-07-09

C. Revision number and Last date revised

- 2 times, 2014-03-11

D. Other

- This MSDS is prepared according to the Globally Harmonized System (GHS).



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.