



Akzonobel Industrial Coatings Korea

# MATERIAL SAFETY DATA SHEET

**A/T#3300 EP-01 AA7224**

Date of issue: 2013-06-25

Revision date: 2014-03-12

Version: R0001.0002

## 1. IDENTIFICATION

### A. Product name

- A/T#3300 EP-01 AA7224 [KF000007160]

### B. Recommended use and restriction on use

- General use : paint applid on plastic resin
- Restriction on use : Do not use for other purposes

### C. Manufacturer / Supplier / Distributor information

#### o Manufacturer information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 60, Bonsan 1-ro 56beon-gil, Jinyeong-eup, Gimhae-si, Gyeongsangnam-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 55-720-0200
- Fax number :
- E-mail address :

#### o Supplier/Distributor information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 11, Byeolmang-ro 459beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 31-490-4200
- Fax number :
- E-mail address :

## 2. HAZARD IDENTIFICATION

### A. GHS Classification

- Acute toxicity (inhalation: vapor) : Category3
- Chronic aquatic toxicity : Category3
- Carcinogenicity : Category1B
- Reproductive toxicity : Category1A
- Germ cell mutagenicity : Category1B
- Serious eye damage/irritation : Category2
- Flammable liquids : Category3
- Specific target organ toxicity(Single exposure) : Category1
- Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)
- Specific target organ toxicity(Repeated exposure) : Category2
- Skin corrosion/irritation : Category2



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

## B. GHS label elements

### ○ Hazard symbols



### ○ Signal words

- Danger

### ○ Hazard statements

- H226 Flammable liquid and vapour
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H331 Toxic if inhaled
- H335 May cause respiratory irritation.
- H340 May cause genetic defects
- H350 May cause cancer
- H360 May damage fertility or the unborn child
- H370 Causes damage to organs(Refer Section SDS 11)
- H373 May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)
- H412 Harmful to aquatic life with long lasting effects

### ○ Precautionary statements

#### 1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

#### 2) Response

- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P307+P311 If exposed: Call a POISON CENTER or doctor/physician.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P311 Call a POISON CENTER or doctor/physician.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).



**3) Storage**

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

**4) Disposal**

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

**C. Other hazards which do not result in classification : (NFPA Classification)**○ **NFPA grade (0 ~ 4 level)**

- Health : 2, Flammability : 3, Reactivity : 0

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

| Chemical Name  | Trade names and Synonyms         | CAS No.    | Content(%) |
|--|----------------------------------|------------|------------|
| n-Butyl acetate  | Acetic acid, butyl ester         | 123-86-4   | 20 ~ 30    |
| Acryl resin  | -                                | -          | 20 ~ 30    |
| 4-Methyl-2-pentanone   | Methylisobutyl ketone, MIBK      | 108-10-1   | 10 ~ 20    |
| 2-Propenoic acid, 2-methyl-, polymer with butyl 2-methyl-2-propenoate, butyl 2-propenoate, 2-hydroxyethyl 2-methyl-2-propenoate and methyl 2-methyl-2-propenoate | -                                | 56422-54-9 | 10 ~ 20    |
| Toluene  | Methylbenzene                    | 108-88-3   | 1 ~ 10     |
| Aluminium  | Allbri aluminum paste and powder | 7429-90-5  | 1 ~ 10     |
| Xylene   | Dimethylbenzene                  | 1330-20-7  | 1 ~ 10     |
| 2-Methyl-2-propenoic acid butyl ester polymer with butyl 2-propenoate, 2-hydroxyethyl 2-methyl-2-propenoate, methyl 2-methyl-2-propenoate and 2-propenoic acid   | -                                | 54868-06-3 | 1 ~ 10     |
| Cellulose acetate butylate   | Cellulose, acetate butanoate     | 9004-36-8  | 1 ~ 10     |
| Ethylene glycol monoethyl ether acetate  | 2-Ethoxyethyl acetate            | 111-15-9   | 1 ~ 10     |
| N-methylpyrrolidone  | N-Methyl-alpha-pyrrolidinone     | 872-50-4   | 1 ~ 10     |
| Stoddard solvent   | Turpentine, mineral              | 8052-41-3  | 1 ~ 10     |
| Solvent naphtha (petroleum), light arom.   | Naphtha                          | 64742-95-6 | 1 ~ 10     |
| Ethylbenzene   | Benzene, ethyl-                  | 100-41-4   | 0 ~ 1      |
| Secret   | Secret                           | -          | 1 ~ 10     |

**4. FIRST AID MEASURES****A. Eye contact**

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms (flare, irritate) occur.
- Remove contact lenses if worn.

**B. Skin contact**

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms (flare, irritate) occur.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

**C. Inhalation contact**

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.
- Take the doctor's examination.

#### **D. Ingestion contact**

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

#### **E. Delayed and immediate effects and also chronic effects from short and long term exposure**

- Not available

#### **F. Notes to physician**

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

### **5. FIREFIGHTING MEASURES**

#### **A. Suitable (Unsuitable) extinguishing media**

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

#### **B. Specific hazards arising from the chemical**

- Not available

#### **C. Special protective actions for firefighters**

- Cool containers with water until well after fire is out.
- Keep unauthorized personnel out.
- Using a unattended and water devices in case of large fire and leave alone to burn if you do not imperative.
- Do not access if the tank on fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

### **6. ACCIDENTAL RELEASE MEASURES**

#### **A. Personal precautions, protective equipment and emergency procedures**

- Wear proper personal protective apparatus as indicated in Section 8 and avoid skin contact and inhalation.
- Ventilate closed spaces before entering.
- Do not touch spilled material. Stop leak if you can do it without risk.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

#### **B. Environmental precautions**

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.



### C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.
- Spilled material should be treated as a potential risk of waste collected.

## 7. HANDLING AND STORAGE

### A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Comply with all applicable laws and regulations for handling
- Get the manual before use.
- Dealing only with a well-ventilated place.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

### B. Conditions for safe storage, including any incompatibilities

- Check regularly for leaks.
- Keep in the original container.
- Please pay attention to incompatibilities materials and conditions to avoid.
- Keep sealed when not in use.
- Prevent static electricity and keep away from combustible materials or heat sources.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### A. Exposure limits

- o ACGIH TLV
  - [n-Butyl acetate] : TWA 150 ppm
  - [4-Methyl-2-pentanone] : TWA 50 ppm
  - [Toluene] : TWA 50 ppm
  - [Aluminium] : TWA : 10 mg/m<sup>3</sup> Aluminium(metal dust)
  - [Xylene] : TWA 100 ppm
  - [Ethylene glycol monoethyl ether acetate] : TWA 5 ppm
  - [Stoddard solvent] : TWA 100 ppm
  - [Ethylbenzene] : TWA 100 ppm
  - [Secret] : TWA 150 ppm
  - [Secret] : TWA 20 ppm
  - [Secret] : TWA 10 mg/m<sup>3</sup>
  - [Secret] : TWA 200 ppm
  - [Secret] : TWA 1000 ppm

### B. Engineering controls



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

### C. Personal protective equipment

#### o Respiratory protection

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

#### o Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

#### o Hand protection

- Wear appropriate chemical resistant glove.

#### o Skin protection

- Wear appropriate chemical resistant protective clothing.

#### o Others

- Not available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |                        |
|---|------------------------|
| A. Appearance                                   |                        |
| - Appearance                                    | Liquid(Viscous liquid) |
| - Color   | Not available          |
| B. Odor   | Not available          |
| C. Odor threshold                               | Not available          |
| D. pH   | Not available          |
| E. Melting point/Freezing point                 | Not available          |
| F. Initial Boiling Point/Boiling Ranges         | Not available          |
| G. Flash point                                  | 32 °C                  |
| H. Evaporation rate                             | Not available          |
| I. Flammability(solid, gas)                     | Not available          |
| J. Upper/Lower Flammability or explosive limits | Not available          |
| K. Vapour pressure                              | Not available          |
| L. Solubility                                   | Not available          |
| M. Vapour density                               | Not available          |
| N. Specific gravity                             | 1.00~0.03              |
| O. Partition coefficient of n-octanol/water     | Not available          |
| P. Autoignition temperature                     | Not available          |
| Q. Decomposition temperature                    | Not available          |
| R. Viscosity                                    | 60~70 KU               |
| S. Molecular weight                             | Not available          |

## 10. STABILITY AND REACTIVITY

### A. Chemical stability

- This material is stable under recommended storage and handling conditions.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

**B. Possibility of hazardous reactions**

- Cylinders exposed to fire may vent and release flammable gas.

**C. Conditions to avoid**

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

**D. Incompatible materials**

- Not available

**E. Hazardous decomposition products**

- May emit flammable vapour if involved in fire.

**11. TOXICOLOGICAL INFORMATION****A. Information on the likely routes of exposure**

- **(Respiratory tracts)**
  - May cause respiratory irritation.
- **(Oral)**
  - Not available
- **(Eye/Skin)**
  - Causes serious eye irritation
  - Causes skin irritation

**B. Delayed and immediate effects and also chronic effects from short and long term exposure**

- **Acute toxicity**
  - \* **Oral**
    - [n-Butyl acetate] : LD50 = 14130 mg/kg Rat
    - [4-Methyl-2-pentanone] : LD50 = 2080 mg/kg Rat
    - [Toluene] : LD50 2600 mg/kg Rat
    - [Xylene] : LD50 3500 mg/kg Rat
    - [Ethylene glycol monoethyl ether acetate] : LD50 = 2700 mg/kg Rat
    - [N-methylpyrrolidone] : LD50 = 7725 mg/kg Rat (Oral)
    - [Stoddard solvent] : LD50 > 5000 mg/kg Rat
    - [Solvent naphtha (petroleum), light arom.] : LD50 = 8400 mg/kg Rat
    - [Ethylbenzene] : LD50 = 3500 mg/kg Rat
    - [Secret] : LD50 = 15400 mg/kg Rat
    - [Secret] : LD50 = 790 mg/kg Rat
    - [Secret] : LD50 > 10000 mg/kg Rat
    - [Secret] : LD50 = 8532 mg/kg Rat
    - [Secret] : LD50 > 5000 mg/kg Rat
    - [Secret] : LD50 > 8800 mg/kg Rat
    - [Secret] : LD50 = 4710mg/kg Rat
    - [Secret] : LD50 = 6200 mg/kg Rat
    - [Secret] : LD50 = 526 mg/kg Rat
    - [Secret] : LD50 6200 mg/kg Rat
    - [Secret] : LD50 = 16000 mg/kg Rat
    - [Secret] : LD50 > 4000 mg/kg Rat
  - \* **Dermal**
    - [n-Butyl acetate] : LD50 = 17600 mg/kg Rabbit
    - [4-Methyl-2-pentanone] : LD50 = 3000 mg/kg rabbit
    - [Toluene] : LD50 120000 mg/kg Rat



- [Xylene] : LD50 4350 mg/kg Rabbit
- [N-methylpyrrolidone] : LD50 = 5000 mg/kg Rat
- [Solvent naphtha (petroleum), light arom.] : LD50 > 2000 mg/kg Rabbit
- [Ethylbenzene] : LD50 = 15400 mg/kg Rabbit
- [Secret] : LD50 = 17400 mg/kg rabbit
- [Secret] : LD50 = 3402 mg/kg rabbit
- [Secret] : LD50 > 10000 mg/kg Rabbit
- [Secret] : LD50 > 5000 mg/kg Rabbit
- [Secret] : LD50 = 12870 mg/kg rabbit
- [Secret] : LD50 = 1488 mg/kg rabbit
- [Secret] : LD50 15800 mg/kg rabbit
- [Secret] : LD50 = 11300 mg/kg rabbit
- [Secret] : LD50 > 3000 mg/kg Rabbit

**\* Inhalation**

- [n-Butyl acetate] : Steam LC50 = 2000 ppm Rat
- [4-Methyl-2-pentanone] : LC50 = 8.2 mg/l Rat
- [Toluene] : LC50 12.5 mg/l 4 hr Rat
- [Xylene] : Steam LC50 6700 ppm 4 hr Rat (Equivalents : 29.09 mg/L)
- [Ethyleneglycol monoethyl ether acetate] : LC50 = 12.1 mg/l Rat (8hr)
- [Solvent naphtha (petroleum), light arom.] : Mist LC50 = 3400 ppm 4 hr Rat
- [Ethylbenzene] : Steam LC50 = 4000 ppm 4 hr Rat (Equivalents : 17.4 mg/L)
- [Secret] : LC50 = 8000 ppm 4 hr Rat
- [Secret] : Steam LC50 = 8000 ppm 4 hr Rat
- [Secret] : LC50 > 6.82 mg/l 4 hr Rat
- [Secret] : Steam LC50 = 4345 ppm 6 hr Rat
- [Secret] : dust LC50  $\geq$  0.477 mg/kg 4 hr Rat
- [Secret] : LC50 = 72600 mg/l 4 hr Rat
- [Secret] : LC50 = 20000 ppm 10 hr Rat
- [Secret] : LC50 64000 ppm 4 hr Rat
- [Secret] : LC50 = 4910 ppm 4 hr Rat

o **Skin corrosion/irritation**

- Causes skin irritation

o **Serious eye damage/irritation**

- Causes serious eye irritation

o **Respiratory sensitization**

- Not available

o **Skin sensitization**

- Not available

o **Carcinogenicity**

**\* IARC**

- [4-Methyl-2-pentanone] : 2B
- [Xylene] : 3
- [Ethylbenzene] : Group 2B
- [Secret] : 2B
- [Secret] : 1
- [Secret] : 3

**\* OSHA**

- Not available

**\* ACGIH**

- [4-Methyl-2-pentanone] : A3
- [Aluminium] : A4
- [Xylene] : A4
- [Ethylbenzene] : A3



- [Secret] : A4
- [Secret] : A4 (Zirconium compounds)
- [Secret] : A3
- \* **NTP**
  - Not available
- \* **EU CLP**
  - [Stoddard solvent] : Carc. 1B
  - [Solvent naphtha (petroleum), light arom.] : Carc. 1B
- **Germ cell mutagenicity**
  - May cause genetic defects
- **Reproductive toxicity**
  - May damage fertility or the unborn child
- **STOT-single exposure**
  - Causes damage to organs(Refer Section SDS 11)
  - May cause respiratory irritation.
- **STOT-repeated exposure**
  - May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)
- **Aspiration hazard**
  - Not available

## 12. ECOLOGICAL INFORMATION

### A. Ecotoxicity

- **Fish**
  - [n-Butyl acetate] : LC50 = 62 mg/l 96 hr
  - [4-Methyl-2-pentanone] : LC50 = 540 mg/l 96 hr
  - [Toluene] : LC50 24 mg/l 96 hr Oncorhynchus mykiss
  - [Xylene] : LC50 3.3 mg/l 96 hr
  - [Ethleneglycol monoethyl ether acetate] : LC50 = 40 mg/l 96 hr
  - [N-methylpyrrolidone] : LC50 = 832 mg/l 96 hr
  - [Solvent naphtha (petroleum), light arom.] : LC50 = 9.22 mg/l 96 hr Oncorhynchus mykiss
  - [Ethylbenzene] : LC50 = 9.09 mg/l 96 hr
  - [Secret] : LC50 = 17 mg/l 96 hr
  - [Secret] : LC50 > 100 mg/l 96 hr
  - [Secret] : LC50 ≥ 100 mg/l 96 hr Oryzias latipes
  - [Secret] : LC50 = 45 mg/l 48 hr Oncorhynchus mykiss
  - [Secret] : LC50 > 100 mg/l 96 hr Other (Salmo trutta)
  - [Secret] : LC50 = 313.683 mg/l 96 hr
  - [Secret] : LC50 = 42 mg/l 96 hr Oncorhynchus mykiss
  - [Secret] : LC50 = 315 mg/l 96 hr Fundulus heteroclitus
  - [Secret] : LC50 15400 mg/l 96 hr Lepomis macrochirus
  - [Secret] : LC50 = 5.57 mg/l 96 hr
  - [Secret] : LC50 > 100 mg/l 96 hr Oryzias latipes
- **Crustaceans**
  - [n-Butyl acetate] : LC50 = 32 mg/l 48 hr
  - [4-Methyl-2-pentanone] : EC50 = 170 mg/l 48 hr
  - [Toluene] : EC50 11.5 mg/l 48 hr Daphnia magna
  - [Xylene] : LC50 190 mg/l 96 hr
  - [N-methylpyrrolidone] : LC50 = 1.23 mg/l 48 hr
  - [Solvent naphtha (petroleum), light arom.] : EC50 = 6.14 mg/l 48 hr Daphnia magna
  - [Stoddard solvent] : LC50 = 0.4 ~ 2.3 mg/l 48 hr
  - [Ethylbenzene] : LC50 = 0.4 mg/l 96 hr
  - [Secret] : EC50 = 1983 mg/l 48 hr



- [Secret] : EC50 > 1000 mg/ℓ 48 hr
- [Secret] : EC50 = 373 mg/ℓ 48 hr Daphnia magna
- [Secret] : EC50 > 100 mg/ℓ 48 hr Daphnia magna
- [Secret] : LC50 = 323.140 mg/ℓ 48 hr
- [Secret] : EC50 = 2 mg/ℓ 48 hr Daphnia magna
- [Secret] : EC50 = 1.2 mg/ℓ 64 hr Daphnia magna
- [Secret] : LD50 > 100 mg/ℓ 96 hr Daphnia magna
- [Secret] : EC50 = 380 mg/ℓ 48 hr Daphnia magna

○ **Algae**

- [N-methylpyrrolidone] : EC50 > 500 mg/ℓ 72 hr
- [Solvent naphtha (petroleum), light arom.] : EC50 = 19 mg/ℓ 72 hr Selenastrum capricornutum
- [Secret] : EC50 = 28 mg/ℓ 48 hr
- [Secret] : EC50 ≥ 1000 mg/ℓ 72 hr Selenastrum capricornutum
- [Secret] : EC50 > 100 mg/ℓ 72 hr Selenastrum capricornutum
- [Secret] : EC50 = 195.497 mg/ℓ 96 hr
- [Secret] : EC50 = 2.2 mg/ℓ 96 hr
- [Secret] : EC50 = 345 mg/ℓ 72 hr Selenastrum capricornutum

## B. Persistence and degradability

○ **Persistence**

- [n-Butyl acetate] : log Kow = 1.78
- [4-Methyl-2-pentanone] : log Kow = 1.38
- [Toluene] : log Kow 2.73
- [Ethylene glycol monoethyl ether acetate] : log Kow = 0.59
- [N-methylpyrrolidone] : log Kow = -0.54
- [Stoddard solvent] : log Kow = 3.16 ~ 7.06
- [Solvent naphtha (petroleum), light arom.] : log Kow = 2.1 ~ 6 (Estimates)
- [Secret] : log Kow = 1.78
- [Secret] : log Kow = 0.43
- [Secret] : log Kow = 7.54
- [Secret] : log Kow = -2.7
- [Secret] : log Kow -0.77
- [Secret] : log Kow = 0.42

○ **Degradability**

- [N-methylpyrrolidone] : BOD5/COD = 0.68
- [Solvent naphtha (petroleum), light arom.] : BOD5/COD = 0.43
- [Secret] : BOD5/COD = 0.57

## C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [N-methylpyrrolidone] : BCF = 0.16
- [Secret] : BCF = 10
- [Secret] : BCF = 3.162
- [Secret] : BCF = 72.5
- [Secret] : BCF = 1.34 ~ 1.54

○ **Biodegradation**

- [n-Butyl acetate] : Biodegradability = 98 (%)
- [Toluene] : 86 (%) 20 day
- [Xylene] : 39 (%)
- [Ethylene glycol monoethyl ether acetate] : Biodegradability = 86.9 (%)
- [N-methylpyrrolidone] : Biodegradability = 73 (%) 28 day
- [Stoddard solvent] : Biodegradability = 12 ~ 13 (%)
- [Secret] : Biodegradability > 60 (%) 28 day



- [Secret] : Biodegradability = 6 (%) 28 day ( Non-biodegradability)
- [Secret] : Biodegradability = 75 (%) 20 day (Aerobic, Other, Easily decomposed)
- [Secret] : Biodegradability = 88 (%)
- [Secret] : Biodegradability = 84 (%) 28 day

#### D. Mobility in soil

- [Xylene] : log Kow = 3.12 (measured) (ortho), 3.2 (measured) (meta), 3.15 (measurements) (p) (5)
- [Ethylbenzene] : log Kow = 3.15 (11)
- [Secret] : Koc = 1

#### E. Other adverse effects

- Not available

### 13. DISPOSAL CONSIDERATIONS

#### A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- High temperature incinerate
- After taking off organic solvents that are supposed to be recycled, incinerate the rest of them at a high degree.

#### B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

### 14. TRANSPORT INFORMATION

#### A. UN number

- 1263

#### B. Proper shipping name

- Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

#### C. Hazard class

- 3

#### D. Packing group

- III

#### E. Marine pollutant

- [Aluminium] : Applicable
- [Stoddard solvent] : Applicable
- [Solvent naphtha (petroleum), light arom.] : Applicable
- [Ethylbenzene] : Applicable

#### F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)



## 15. REGULATORY INFORMATION

### A. National and/or international regulatory information

#### o POPs Management Law

- Not applicable

#### o Information of EU Classification

##### \* Classification

- [n-Butyl acetate] : R10 R66 R67
- [4-Methyl-2-pentanone] : F; R11 Xn; R20 Xi; R36/37 R66
- [Toluene] : F; R11 Repr.Cat.3; R63 Xn; R48/20-65 Xi; R38 R67
- [Aluminium] : F; R15-17
- [Xylene] : R10 Xn; R20/21 Xi; R38
- [Ethyleneglycol monoethyl ether acetate] : R10 Repr. Cat. 2; R60-61 Xn; R20/21/22
- [N-methylpyrrolidone] : Repr. Cat. 2; R61, Xi; R36/37/38
- [Stoddard solvent] : Carc. Cat. 2; R45 Muta. Cat. 2; R46 Xn; R65
- [Solvent naphtha (petroleum), light arom.] : Carc. Cat. 2; R45/Muta. Cat. 2; R46, Xn; R65
- [Ethylbenzene] : F; R11 Xn; R20
- [Secret] : F; R11 R66
- [Secret] : R10 Xn; R 22 Xi; R37/38-41 R67
- [Secret] : R10
- [Secret] : F; R11 Xi; R36 R67
- [Secret] : F; R11
- [Secret] : F; R11 T; R23/24/25-39/23/24/25
- [Secret] : R10 Xi; R36/37/38 R43
- [Secret] : Xi; R36/38 R43

##### \* Risk Phrases

- [n-Butyl acetate] : R10, R66, R67
- [4-Methyl-2-pentanone] : R11, R20, R36/37, R66
- [Toluene] : R11, R38, R48/20, R63, R65, R67
- [Aluminium] : R15, R17
- [Xylene] : R10, R20/21, R38
- [Ethyleneglycol monoethyl ether acetate] : R60, R61, R10, R20/21/22
- [N-methylpyrrolidone] : R61, R36/37/38
- [Stoddard solvent] : R45, R46, R65
- [Solvent naphtha (petroleum), light arom.] : R45, R65, R46
- [Ethylbenzene] : R11, R20
- [Secret] : R11, R66
- [Secret] : R10, R22, R37/38, R41, R67
- [Secret] : R10
- [Secret] : R11, R36, R67
- [Secret] : R11
- [Secret] : R11, R23/24/25, R39/23/24/25
- [Secret] : R10, R36/37/38, R43
- [Secret] : R36/38, R43

##### \* Safety Phrase

- [n-Butyl acetate] : S2, S25
- [4-Methyl-2-pentanone] : S2, S9, S16, S29
- [Toluene] : S2, S36/37, S46, S62
- [Aluminium] : S2, S7/8, S43
- [Xylene] : S2, S25
- [Ethyleneglycol monoethyl ether acetate] : S53, S45
- [N-methylpyrrolidone] : S53, S45
- [Stoddard solvent] : S53, S45



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Solvent naphtha (petroleum), light arom.] : S53, S45
- [Ethylbenzene] : S2, S16, S24/25, S29
- [Secret] : S2, S16, S23, S25, S29, S33
- [Secret] : S2, S7/9, S13, S26, S37/39, S46
- [Secret] : S2
- [Secret] : S2, S7, S16, S24/25, S26
- [Secret] : S2, S7, S16
- [Secret] : S1/2, S7, S16, S36/37, S45
- [Secret] : S2, S26, S28
- **U.S. Federal regulations**
  - \* **OSHA PROCESS SAFETY (29CFR1910.119)**
    - Not applicable
  - \* **CERCLA Section 103 (40CFR302.4)**
    - [n-Butyl acetate] : 2267.995 kg 5000 lb
    - [4-Methyl-2-pentanone] : 2267.995 kg 5000 lb
    - [Toluene] : 453.599 kg 1000 lb
    - [Xylene] : 45.3599 kg 100 lb
    - [Ethylbenzene] : 453.599 kg 1000 lb
    - [Secret] : 2267.995 kg 5000 lb
  - \* **EPCRA Section 302 (40CFR355.30)**
    - Not applicable
  - \* **EPCRA Section 304 (40CFR355.40)**
    - Not applicable
  - \* **EPCRA Section 313 (40CFR372.65)**
    - [4-Methyl-2-pentanone] : Applicable
    - [Toluene] : Applicable
    - [Aluminium] : Applicable
    - [Xylene] : Applicable
    - [N-methylpyrrolidone] : Applicable
    - [Ethylbenzene] : Applicable
    - [Secret] : Applicable
- **Rotterdam Convention listed ingredients**
  - Not applicable
- **Stockholm Convention listed ingredients**
  - Not applicable
- **Montreal Protocol listed ingredients**
  - Not applicable

## 16. OTHER INFORMATION

### A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

### B. Issue date

- 2013-06-25

### C. Revision number and Last date revised

- 1 times, 2014-03-12

### D. Other

- This MSDS is prepared according to the Globally Harmonized System (GHS).



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.