



Akzonobel Industrial Coatings Korea

MATERIAL SAFETY DATA SHEET

SENOSOFT SF-15 M15

Date of issue: 2015-04-01

Revision date: 2015-04-01

Version: R0001.0002

1. IDENTIFICATION

A. Product name

- SENOSOFT SF-15 M15

B. Recommended use and restriction on use

- General use : paint applid on plastic resin
- Restriction on use : Do not use for other purposes

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 60, Bonsan 1-ro 56beon-gil, Jinyeong-eup, Gimhae-si, Gyeongsangnam-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 55-720-0200
- Fax number :
- E-mail address :

○ Supplier/Distributor information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 11, Byeolmang-ro 459beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 31-490-4200
- Fax number :
- E-mail address :

2. HAZARD IDENTIFICATION

A. GHS Classification


- Acute toxicity (inhalation: vapor) : Category4
- Chronic aquatic toxicity : Category2
- Carcinogenicity : Category1B
- Reproductive toxicity : Category1A
- Germ cell mutagenicity : Category1B
- Serious eye damage/irritation : Category2
- Flammable liquids : Category3
- Specific target organ toxicity(Single exposure) : Category1
- Specific target organ toxicity(Repeated exposure) : Category1
- Skin corrosion/irritation : Category2

B. GHS label elements



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

○ **Hazard symbols**



○ **Signal words**

- Danger

○ **Hazard statements**

- H226 Flammable liquid and vapour
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H340 May cause genetic defects
- H350 May cause cancer
- H360 May damage fertility or the unborn child
- H370 Causes damage to organs(Refer Section SDS 11)
- H372 Causes damage to organs through prolonged or repeated exposure (Refer Section SDS 11)
- H411 Toxic to aquatic life with long lasting effects

○ **Precautionary statements**

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

2) Response

- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P307+P311 If exposed: Call a POISON CENTER or doctor/physician.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).
- P391 Collect spillage.

3) Storage

- P403+P235 Store in a well-ventilated place. Keep cool.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

o NFPA grade (0 ~ 4 level)

- Health : 2, Flammability : 2, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
4-Methyl-2-pentanone	Methylisobutyl ketone, MIBK	108-10-1	10 ~ 20
Toluene	Methylbenzene	108-88-3	10 ~ 20
1,3-Dioxolan-2-one polymer with 1,6-hexanediol and 1,5-pentanediol	-	132459-81-5	10 ~ 20
Urethane acrylate	-	146268-21-9	10 ~ 20
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	1 ~ 10
Silicon dioxide	Precipitated silica	112926-00-8	1 ~ 10
DIACETONE ALCOHOL	4-Hydroxy-4-methyl-2-pentanone	123-42-2	1 ~ 10
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	1 ~ 10
POLYESTER POLYOL	-	-	1 ~ 10
Carbon black	Acetylene black	1333-86-4	1 ~ 10
Xylene	Dimethylbenzene	1330-20-7	1 ~ 10
Polyurethane Resin	-	-	1 ~ 10
pe/amide wax	-	-	1 ~ 10
Stoddard solvent	Turpentine, mineral	8052-41-3	0 ~ 1
Naphtha (petroleum), hydrodesulfurized heavy	Aliphatic hydrocarbon	64742-82-1	0 ~ 1
Secret	Secret	-	1 ~ 10

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms (flare, irritate) occur.
- Remove contact lenses if worn.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms (flare, irritate) occur.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

D. Ingestion contact

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES**A. Suitable (Unsuitable) extinguishing media**

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Cool containers with water until well after fire is out.
- Keep unauthorized personnel out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

6. ACCIDENTAL RELEASE MEASURES**A. Personal precautions, protective equipment and emergency procedures**

- Wear proper personal protective apparatus as indicated in Section 8 and avoid skin contact and inhalation.
- Do not touch spilled material. Stop leak if you can do it without risk.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.
- Spilled material should be treated as a potential risk of waste collected.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Refer to Engineering controls and personal protective equipment.
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.
- Operators should wear antistatic footwear and clothing.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Save in cool, dry and well ventilated place.
- Do not use damaged containers.
- Do not apply direct heat.
- No open fire.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- o **ACGIH TLV**
 - [4-Methyl-2-pentanone] : TWA, 20 ppm, STEL 75 ppm
 - [Toluene] : TWA 20 ppm (75 mg/m³)
 - [Isobutyl acetate] : TWA, 150 ppm (713 mg/m³)
 - [DIACETONE ALCOHOL] : TWA, 50 ppm (238 mg/m³)
 - [n-Butyl acetate] : TWA, 150 ppm (713 mg/m³), STEL, 200 ppm (950 mg/m³)
 - [Carbon black] : TWA, 3 mg/m³, Inhalable particulate matter
 - [Xylene] : TWA 100 ppm (434 mg/m³), STEL, 150 ppm (651 mg/m³)
 - [Secret] : TWA 10 mg/m³
 - [Secret] : TWA, 1 mg/m³, Respirable Particulate Matter
 - [Stoddard solvent] : TWA 100 ppm (525 mg/m³)
 - [Secret] : TWA, 100 ppm (606 mg/m³)
 - [Secret] : TWA 5 ppm (19 mg/m³)
 - [Secret] : TWA 0.025 mg/m³, Respirable particulate matter

B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Personal protective equipment

- o **Respiratory protection**
 - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
 - Respiratory protection is ranked in order from minimum to maximum.
 - Consider warning properties before use.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- **Eye protection**
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
- **Hand protection**
 - Wear appropriate chemical resistant glove.
- **Skin protection**
 - Wear appropriate chemical resistant protective clothing.
- **Others**
 - Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(Viscous liquid)
- Color	Black
B. Odor	Not available
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	Not available
G. Flash point	23 °C ~ 70 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity(Relative density)	1±0.03
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	58.4±3 KU
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY

A. Chemical Stability and Reactivity

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION**A. Information on the likely routes of exposure**

- **(Respiratory tracts)**
 - Not available
- **(Oral)**
 - Not available
- **(Eye/Skin)**
 - Causes serious eye irritation
 - Causes skin irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- **Acute toxicity**
 - * **Oral**
 - [4-Methyl-2-pentanone] : LD50 = 2080 mg/kg Rat
 - [Toluene] : rat LD50=2600 mg/kg
 - [Isobutyl acetate] : LD50 = 15400 mg/kg Rat
 - [DIACETONE ALCOHOL] : LD50 = 2520 mg/kg Rat
 - [n-Butyl acetate] : LD50 = 14130 mg/kg Rat
 - [Carbon black] : LD50 = 15400 mg/kg Rat
 - [Xylene] : LD50=3550 mg/kg rat
 - [Secret] : LD50 > 10000 mg/kg Rat
 - [Secret] : LD50 = 5000 mg/kg Rat
 - [Secret] : LD50 > 2000 mg/kg Rat
 - [Secret] : LD50 = 2369 mg/kg Rat
 - [Secret] : LD50 > 5000 mg/kg Rat
 - [Naphtha (petroleum), hydrodesulfurized heavy] : LD50 = 5000 mg/kg Rat
 - [Stoddard solvent] : LD50 > 5000 mg/kg Rat
 - [Secret] : LD50 = 2000 ~ 3000 mg/kg Rat (female)
 - [Secret] : LD50 = 5180mg/kg Rat
 - [Secret] : LD50 = 600 mg/kg Rat
 - [Secret] : LD50 = 8400 mg/kg Rat
 - [Secret] : LD50 3500 mg/kg Rat
 - [Secret] : LD50 = 58 mg/kg Rat
 - [Secret] : LD50 = 8250 mg/kg Rat
 - [Secret] : LD50 = 2417 mg/kg Rat
 - [Secret] : LD50 5000 mg/kg Rat
 - [Secret] : LD50 317 mg/kg Rat
 - * **Dermal**
 - [4-Methyl-2-pentanone] : LD50 = 3000 mg/kg rabbit
 - [Toluene] : rabbit LD50=12,000 mg/kg
 - [Isobutyl acetate] : LD50 = 17400 mg/kg rabbit
 - [Silicon dioxide] : LD50 = 5000 mg/kg
 - [DIACETONE ALCOHOL] : LD50 = 13630 mg/kg Rabbit
 - [n-Butyl acetate] : LD50 = 17600 mg/kg Rabbit
 - [Carbon black] : LD50 = 3000 mg/kg rabbit
 - [Xylene] : LD50 4350 mg/kg Rabbit



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Secret] : LD50 > 10000 mg/kg Rabbit
- [Secret] : LD50 > 2000 mg/kg Rat
- [Naphtha (petroleum), hydrosulfurized heavy] : LD50 = 3160 mg/kg rabbit
- [Secret] : LD50 = 9500 mg/kg Rabbit
- [Secret] : LD50 > 2000 mg/kg Rabbit
- [Secret] : LD50 = 777 mg/kg rabbit
- [Secret] : LD50 15440 mg/kg Rabbit
- [Secret] : LD50 > 10200 mg/kg Rabbit
- [Secret] : LD50 670 mg/kg Rat

*** Inhalation**

- [4-Methyl-2-pentanone] : LC50 = 8.2 mg/ℓ Rat
- [Toluene] : rat LC50=28.1 mg/L/4hr
- [Isobutyl acetate] : LC50 = 38.0 mg/L/4 hr Rat
- [Silicon dioxide] : Steam LC50 > 2.0 mg/ℓ Rat
- [n-Butyl acetate] : Steam LC50 = 0.74 mg/L/4hr Rat (GLP)
- [Xylene] : Steam LC50 6700 ppm 4 hr Rat (Equivalents : 29.09 mg/L)
- [Secret] : LC50 > 6.82 mg/ℓ 4 hr Rat
- [Secret] : dust LC50 ≥ 0.477 mg/L 4 hr Rat
- [Secret] : dust LC50 > 12.6 mg/ℓ 4 hr Rat (GLP data)
- [Secret] : LC50 > 5.2 mg/L 4 hr Rat, LC50=3400 ppm 4hr
- [Secret] : Mist LC50 = 0.059 ~ 22 mg/L Rat
- [Secret] : Steam LC50 > 0.379 mg/ℓ Rat
- [Secret] : Steam LC50 36.9 mg/L/4 hr Rat
- [Secret] : dust LC50 0.316 mg/ℓ Rat

○ **Skin corrosion/irritation**

- Causes skin irritation

○ **Serious eye damage/irritation**

- Causes serious eye irritation

○ **Respiratory sensitization**

- Not available

○ **Skin sensitization**

- Not available

○ **Carcinogenicity**

*** IARC**

- [4-Methyl-2-pentanone] : Group 2B
- [Toluene] : Group 3
- [Silicon dioxide] : Group 3 (Silica, amorphous)
- [Carbon black] : Group 2B
- [Xylene] : Group 3
- [Secret] : Group 2B
- [Secret] : Group 3
- [Secret] : Group 1

*** OSHA**

- Not available

*** ACGIH**

- [4-Methyl-2-pentanone] : A3
- [Toluene] : A4
- [Carbon black] : A3
- [Xylene] : A4
- [Secret] : A4
- [Secret] : A4 (Tin organic compounds)
- [Secret] : A2

*** NTP**



- [Secret] : K

*** EU CLP**

- [Stoddard solvent] : Carc. 1B

- [Naphtha (petroleum), hydrodesulfurized heavy] : Carc. 1B

- [Secret] : Carc. 1B

○ **Germ cell mutagenicity**

- May cause genetic defects

○ **Reproductive toxicity**

- May damage fertility or the unborn child

○ **STOT-single exposure**

- Causes damage to organs(Refer Section SDS 11)

○ **STOT-repeated exposure**

- Causes damage to organs through prolonged or repeated exposure (Refer Section SDS 11)

○ **Aspiration hazard**

- Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

○ **Fish**

- [4-Methyl-2-pentanone] : LC50 = 540 mg/ℓ 96 hr

- [Toluene] : LC50 24 mg/ℓ 96 hr Oncorhynchus mykiss

- [Isobutyl acetate] : LC50 = 17 mg/ℓ 96 hr

- [DIACETONE ALCOHOL] : LC50 = 420 mg/ℓ 96 hr

- [n-Butyl acetate] : LC50 = 62 mg/ℓ 96 hr

- [Xylene] : LC50 3.3 mg/ℓ 96 hr

- [Secret] : LC50 > 93.2 mg/ℓ 96 hr Brachydanio rerio

- [Secret] : LC50 = 0.97 mg/ℓ 96 hr Lepomis macrochirus

- [Secret] : LC50 = 344 mg/ℓ 96 hr

- [Secret] : LC50 = 0.996 mg/ℓ 96 hr

- [Secret] : LC50 > 20000 mg/ℓ 96 hr Oncorhynchus mykiss

- [Secret] : LC50 = 9.22 mg/ℓ 96 hr Oncorhynchus mykiss

- [Secret] : LC50 > 3 mg/ℓ 96 hr Brachydanio rerio

- [Secret] : LC50 11619 mg/ℓ 96 hr Pimephales promelas

- [Secret] : LC50 = 0.000206 mg/ℓ 96 hr Other

- [Secret] : LC50 4.8 mg/ℓ 96 hr Brachydanio rerio

- [Secret] : LC50 10.9 mg/ℓ 96 hr

○ **Crustaceans**

- [4-Methyl-2-pentanone] : EC50 = 170 mg/ℓ 48 hr

- [Toluene] : EC50 11.5 mg/ℓ 48 hr Daphnia magna

- [n-Butyl acetate] : LC50 = 32 mg/ℓ 48 hr

- [Carbon black] : EC50 = 5600 mg/ℓ 24 hr

- [Xylene] : LC50 190 mg/ℓ 96 hr

- [Secret] : EC50 > 1000 mg/ℓ 48 hr

- [Secret] : EC50 0.017 ~ 0.018 mg/ℓ 48 hr Daphnia magna

- [Secret] : EC50 = 20 mg/ℓ 24 hr

- [Stoddard solvent] : LC50 = 0.4 ~ 2.3 mg/ℓ 48 hr

- [Secret] : EC50 > 500 mg/ℓ 48 hr (Cyclops)

- [Secret] : LC50 = 1919 mg/ℓ 48 hr Other (Species : Daphnia)

- [Secret] : LC50 = 0.110 mg/ℓ 48 hr

- [Secret] : EC50 = 6.14 mg/ℓ 48 hr Daphnia magna

- [Secret] : LC50 > 10000 mg/ℓ 48 hr Daphnia magna

- [Secret] : EC50 > 0.21 mg/ℓ 48 hr Daphnia magna



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Secret] : LC50 = 0.2 mg/ℓ 96 hr *Daphnia magna*
- [Secret] : LC50 = 0.000347 mg/ℓ 48 hr Other
- [Secret] : EC50 ≥ 3.2 mg/ℓ 48 hr *Daphnia magna*
- [Secret] : LC50 3.1 mg/ℓ 48 hr

○ **Algae**

- [Secret] : EC50 = 0.017 mg/ℓ 96 hr
- [Secret] : EC50 = 500 mg/ℓ 72 hr
- [Secret] : EC50 = 0.615 mg/ℓ 96 hr
- [Secret] : EC50 = 19 mg/ℓ 72 hr *Selenastrum capricornutum*
- [Secret] : EC50 > 0.56 mg/ℓ 72 hr Other (Freshwater algae)
- [Secret] : EC50 9067 mg/ℓ 72 hr Other (ECOSAR)
- [Secret] : EC50 = 45 mg/ℓ 72 hr *Scenedesmus subspicatus*
- [Secret] : EC50 = 0.000316 mg/ℓ 96 hr Other
- [Secret] : EC50 370 mg/ℓ 96 hr

B. Persistence and degradability

○ **Persistence**

- [4-Methyl-2-pentanone] : log Kow = 1.38
- [Toluene] : log Kow 2.73
- [Isobutyl acetate] : log Kow = 1.78
- [n-Butyl acetate] : log Kow = 1.78
- [Secret] : log Kow = 0.37 (at 25 °C)
- [Stoddard solvent] : log Kow = 3.16 ~ 7.06
- [Secret] : log Kow = 1.16
- [Secret] : log Kow = 5.14
- [Secret] : log Kow = 2.1 ~ 6 (Estimates)
- [Secret] : log Kow = 0.97 (11.43)
- [Secret] : log Kow 0.31 (Estimates)
- [Secret] : log Kow = 8.52 (Estimates)
- [Secret] : log Kow 4.57
- [Secret] : log Kow 1.46

○ **Degradability**

- [Secret] : (75% (20days))
- [Secret] : BOD5/COD = 0.43

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [Secret] : BCF 100
- [Secret] : BCF = 1351
- [Secret] : BCF = 0.3493
- [Secret] : BCF = 180.1
- [Secret] : BCF 1.162
- [Secret] : BCF = 31
- [Secret] : BCF = 16.9
- [Secret] : BCF 3.162

○ **Biodegradation**

- [Toluene] : 86 (%) 20 day
- [DIACETONE ALCOHOL] : Biodegradability = 100 (%) 14 day (Aerobic, Easily decomposed)
- [n-Butyl acetate] : Biodegradability = 98 (%)
- [Xylene] : 39 (%)
- [Secret] : 19 (%) 28 day
- [Secret] : Biodegradability = 38 (%) 28 day
- [Stoddard solvent] : Biodegradability = 12 ~ 13 (%)



- [Secret] : (DPGME Rapidly biodegradable.)
- [Secret] : > 60 (%) 28 day
- [Secret] : Biodegradability = 10 (%) 28 day
- [Secret] : 41 ~ 42 (%) 28 day
- [Secret] : 85 (%)

D. Mobility in soil

- [Xylene] : log Kow = 3.12 (measured) (ortho), 3.2 (measured) (meta), 3.15 (measurements) (p) (5)

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- High temperature incinerate
- After taking off organic solvents that are supposed to be recycled, incinerate the rest of them at a high degree.

B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN number

- 1263

B. Proper shipping name

- Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

C. Hazard class

- 3

D. Packing group

- III

E. Marine pollutant

- Applicable
- [Secret] : Applicable
- [Stoddard solvent] : Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

15. REGULATORY INFORMATION



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

A. National and/or international regulatory information

○ POPs Management Law

- Not applicable

○ Information of EU Classification

* Classification

- [4-Methyl-2-pentanone] : F; R11 Xn; R20 Xi; R36/37 R66
- [Toluene] : F; R11 Repr.Cat.3; R63 Xn; R48/20-65 Xi; R38 R67
- [Isobutyl acetate] : F; R11 R66
- [DIACETONE ALCOHOL] : Xi; R36
- [n-Butyl acetate] : R10 R66 R67
- [Xylene] : R10 Xn; R20/21 Xi; R38
- [Secret] : F; R15-17
- [Naphtha (petroleum), hydrodesulfurized heavy] : Carc. Cat. 2; R45 - Muta. Cat. 2; R46 - Xn; R65
- [Stoddard solvent] : Carc. Cat. 2; R45 Muta. Cat. 2; R46 Xn; R65
- [Secret] : Xn; R22 Xi; R36
- [Secret] : Carc. Cat. 2; R45/Muta. Cat. 2; R46, Xn; R65
- [Secret] : Muta.Cat.3; R68 T; R23/24/25 Xn; R48/20/21/22 C; R34

* Risk Phrases

- [4-Methyl-2-pentanone] : R11, R20, R36/37, R66
- [Toluene] : R11, R38, R48/20, R63, R65, R67
- [Isobutyl acetate] : R11, R66
- [DIACETONE ALCOHOL] : R36
- [n-Butyl acetate] : R10, R66, R67
- [Xylene] : R10, R20/21, R38
- [Secret] : R15, R17
- [Stoddard solvent] : R45, R46, R65
- [Naphtha (petroleum), hydrodesulfurized heavy] : R45, R46, R65
- [Secret] : R22, R36
- [Secret] : R45, R65, R46
- [Secret] : R23/24/25, R34, R48/20/21/22, R68

* Safety Phrase

- [4-Methyl-2-pentanone] : S2, S9, S16, S29
- [Toluene] : S2, S36/37, S46, S62
- [Isobutyl acetate] : S2, S16, S23, S25, S29, S33
- [DIACETONE ALCOHOL] : S2, S24/25
- [n-Butyl acetate] : S2, S25
- [Xylene] : S2, S25
- [Secret] : S2, S7/8, S43
- [Stoddard solvent] : S53, S45
- [Naphtha (petroleum), hydrodesulfurized heavy] : S53, S45
- [Secret] : S2, S26
- [Secret] : S53, S45
- [Secret] : S1/2, S24/25, S26, S28, S36/37/39, S45

○ U.S. Federal regulations

* OSHA PROCESS SAFETY (29CFR1910.119)

- Not applicable

* CERCLA Section 103 (40CFR302.4)

- [4-Methyl-2-pentanone] : 2267.995 kg 5000 lb
- [Toluene] : 453.599 kg 1000 lb
- [Isobutyl acetate] : 2267.995 kg 5000 lb
- [n-Butyl acetate] : 2267.995 kg 5000 lb
- [Xylene] : 45.3599 kg 100 lb
- [Secret] : 453.599 kg 1000 lb



*** EPCRA Section 302 (40CFR355.30)**

- [Secret] : 226.7995/4535.99 kg 500/10000 lb

*** EPCRA Section 304 (40CFR355.40)**

- [Secret] : 453.599 kg 1000 lb

*** EPCRA Section 313 (40CFR372.65)**

- [4-Methyl-2-pentanone] : Applicable

- [Toluene] : Applicable

- [Xylene] : Applicable

- [Secret] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2015-04-01

C. Revision number and Last date revised

- 1 times, 2015-04-01

D. Other

- This MSDS is prepared according to the Globally Harmonized System (GHS).



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.