



Akzonobel Industrial Coatings Korea

MATERIAL SAFETY DATA SHEET

TX-F PRIMER PP DARK GRAY(D/T)

Date of issue: 2016-09-02

Revision date: 2016-09-02

Version: R0001.0002

1. IDENTIFICATION

A. Product name

- TX-F PRIMER PP DARK GRAY(D/T)

B. Recommended use and restriction on use

- General use : paint applid on plastic resin
- Restriction on use : Do not use for other purposes

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 60, Bonsan 1-ro 56beon-gil, Jinyeong-eup, Gimhae-si, Gyeongsangnam-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 55-720-0200
- Fax number :
- E-mail address :

○ Supplier/Distributor information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 11, Byeolmang-ro 459beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 31-490-4200
- Fax number :
- E-mail address :

2. HAZARD IDENTIFICATION

A. GHS Classification

- Acute toxicity (dermal) : Category4
- Acute toxicity (inhalation: vapor) : Category3
- Acute aquatic toxicity : Category1
- Carcinogenicity : Category1B
- Serious eye damage/irritation : Category2
- Flammable liquids : Category3
- Specific target organ toxicity(Single exposure) : Category1
- Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)
- Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)
- Skin corrosion/irritation : Category2
- Aspiration hazard : Category2



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

B. GHS label elements

○ Hazard symbols



○ Signal words

- Warning
- Danger

○ Hazard statements

- H226 Flammable liquid and vapour
- H305 May be harmful if swallowed and enters airways
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H331 Toxic if inhaled
- H335 May cause respiratory irritation.
- H336 May cause drowsiness and dizziness.
- H350 May cause cancer
- H370 Causes damage to organs(Refer Section SDS 11)
- H400 Very toxic to aquatic life

○ Precautionary statements

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe gas/mist/vapours/spray.
- P261 Avoid breathing gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P307+P311 If exposed: Call a POISON CENTER or doctor/physician.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P311 Call a POISON CENTER or doctor/physician.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment
- P322 Specific measures
- P331 Do NOT induce vomiting.
- P332+P313 If skin irritation occurs: Get medical advice/attention.



- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).
- P391 Collect spillage.

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

o NFPA grade (0 ~ 4 level)

- Health : 2, Flammability : 2, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Hexahydrobenzene	Cyclohexane	110-82-7	20 ~ 30
Cyclohexanone	Hexanon	108-94-1	20 ~ 30
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	10 ~ 20
2,5-Furandione reaction products with polypropylene, chlorinated	-	68609-36-9	10 ~ 20
Talc	Talcum	14807-96-6	1 ~ 10
Solvent naphtha (petroleum), light arom.	Naphtha	64742-95-6	1 ~ 10
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	1 ~ 10
Titanium dioxide	Titanium oxide (TiO ₂)	13463-67-7	1 ~ 10
Propylene glycol methyl ether acetate	Propylene glycol monomethyl ether acetate	108-65-6	1 ~ 10
4-Methyl-2-pentanone	Methylisobutyl ketone, MIBK	108-10-1	1 ~ 10
Acetic acid ethyl ester	Ethyl acetate	141-78-6	1 ~ 10
Silicon dioxide	Silic anhydride	7631-86-9	1 ~ 10
Ethanol	Alcohol anhydrous	64-17-5	0 ~ 1
Secret	Secret	-	1 ~ 10

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contact lenses if worn.

B. Skin contact

- Flush skin with plenty of wter for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Prevent the spread of the skin.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.
- Take the doctor's examination.

D. Ingestion contact

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Cool containers with water until well after fire is out.
- Keep unauthorized personnel out.
- Do not access if the tank on fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Must work against the wind, let the upwind people to evacuate.
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Handling the damaged containers or spilled material after wearing protective equipment.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

B. Environmental precautions



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Avoid entering to sewers or water system.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.
- Spilled material should be treated as a potential risk of waste collected.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Comply with all applicable laws and regulations for handling
- Get the manual before use.
- Refer to Engineering controls and personal protective equipment.
- Do not handle until all safety precautions have been read and understood.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Save in cool, dry and well ventilated place.
- Check regularly for leaks.
- Please pay attention to incompatibilities materials and conditions to avoid.
- Keep sealed when not in use.
- No open fire.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.
- Store in well ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- o ACGIH TLV
 - [Hexahydrobenzene] : TWA, 100 ppm (350 mg/m³)
 - [Cyclohexanone] : TWA, 20 ppm (80 mg/m³) STEL, 50 ppm (200 mg/m³) Skin
 - [n-Butyl acetate] : TWA, 150 ppm (713 mg/m³), STEL, 200 ppm (950 mg/m³)
 - [Talc] : TWA 2 mg/m³, Respirable particulate matter (containing no asbestos and <1% crystalline silica)
 - [Isobutyl acetate] : TWA, 150 ppm (713 mg/m³)
 - [Titanium dioxide] : TWA 10 mg/m³
 - [4-Methyl-2-pentanone] : TWA, 20 ppm (82 mg/m³) STEL 75 ppm (307 mg/m³)
 - [Acetic acid ethyl ester] : TWA, 400 ppm (1440 mg/m³)
 - [Ethanol] : STEL, 1000 ppm (1880 mg/m³)
 - [Secret] : TWA, 3 mg/m³, Inhalable particulate matter
 - [Secret] : TWA, 200 ppm (491 mg/m³), STEL, 400 ppm (984 mg/m³)



- [Secret] : TWA, 200 ppm (262 mg/m³) STEL, 250 ppm (328 mg/m³) Skin

B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Personal protective equipment

o Respiratory protection

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

o Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

o Hand protection

- Wear appropriate chemical resistant glove.

o Skin protection

- Wear appropriate chemical resistant protective clothing.

o Others

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(Viscous liquid)
- Color	DARK GRAY
B. Odor	Not available
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	79 °C
G. Flash point	23 °C ~ 70 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity(Relative density)	0.92±0.03
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	420 °C
Q. Decomposition temperature	Not available
R. Viscosity	46.2±3 KU
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

A. Chemical Stability and Reactivity

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- **(Respiratory tracts)**
 - May be harmful if swallowed and enters airways
 - May cause respiratory irritation.
- **(Oral)**
 - Not available
- **(Eye:Skin)**
 - Causes serious eye irritation
 - Causes skin irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- **Acute toxicity**
 - * **Oral**
 - [Cyclohexanone] : LD50 = 1800 mg/kg Rat (RTECS)
 - [Hexahydrobenzene] : LD50 = 12705 mg/kg
 - [n-Butyl acetate] : LD50 = 14130 mg/kg Rat (HSDB)
 - [Solvent naphtha (petroleum), light arom.] : LD50 = 8400 mg/kg Rat
 - [Isobutyl acetate] : LD50 = 15400 mg/kg Rat (DFGOT vol.19 (2003))
 - [Titanium dioxide] : LD50 > 10000 mg/kg Rat (HSDB)
 - [Propylene glycol methyl ether acetate] : LD50 = 8532 mg/kg Rat (IUCLID)
 - [4-Methyl-2-pentanone] : LD50 = 2080 mg/kg Rat (NITE)
 - [Acetic acid ethyl ester] : LD50 5620 mg/kg Rat
 - [Silicon dioxide] : LD50 = 3160 mg/kg Rat (TOMES; HAZARTEXT)
 - [Ethanol] : LD50 = 6200 mg/kg Rat (HSDB)
 - [Secret] : LD50 = 15400 mg/kg Rat (NITE(2006))
 - [Secret] : LD50 = 1920 mg/kg Rat (IUCLID)
 - [Secret] : LD50 > 5000 mg/kg Rat (OECD TG 401; IUCLID; HSDB)
 - [Secret] : LD50 = 4710mg/kg Rat (HSDB)
 - [Secret] : LD50 > 5000 mg/kg Rat (IUCLID,NLM,THOMSON)
 - [Secret] : LD50 6200 mg/kg Rat
 - [Secret] : LD50 > 5000 mg/kg Rat (IUCLID)
 - * **Dermal**
 - [Hexahydrobenzene] : LD50 > 2000 mg/kg Rabbit
 - [Cyclohexanone] : LD50 = 947 mg/kg Rabbit (RTECS)



- [n-Butyl acetate] : LD50 = 17600 mg/kg Rabbit (NITE(2006))
- [Solvent naphtha (petroleum), light arom.] : LD50 > 2000 mg/kg Rabbit
- [Isobutyl acetate] : LD50 = 17400 mg/kg rabbit (DFGOT vol.19 (2003))
- [Titanium dioxide] : LD50 > 10000 mg/kg Rabbit (IUCLID)
- [Propylene glycol methyl ether acetate] : LD50 > 5000 mg/kg Rabbit (IUCLID)
- [4-Methyl-2-pentanone] : LD50 = 3000 mg/kg rabbit (NITE)
- [Acetic acid ethyl ester] : LD50 > 18000 mg/kg Rabbit
- [Silicon dioxide] : LD50 > 2000 mg/kg Rabbit (IUCLID)
- [Secret] : LD50 > 3000 mg/kg rabbit (NITE)
- [Secret] : LD50 = 8500 mg/kg Rat (IUCLID)
- [Secret] : LD50 = 12870 mg/kg rabbit (HSDB)
- [Secret] : LD50 > 5000 mg/kg Rabbit (IUCLID,NLM,THOMSON)
- [Secret] : LD50 15800 mg/kg rabbit

*** Inhalation**

- [Hexahydrobenzene] : LC50 = 70 mg/l
- [Cyclohexanone] : Steam LC50 = 2.375 mg/l Mouse (RTECS)
- [n-Butyl acetate] : LC50 > 21 mg/L/4hr (GLP)(ECHA)
- [Solvent naphtha (petroleum), light arom.] : LC50 > 5.2 mg/L 4 hr Rat, LC50=3400 ppm 4hr
- [Isobutyl acetate] : LC50 = 38.0 mg/L/4 hr Rat (DFGOT vol.19 (2003))
- [Titanium dioxide] : LC50 > 6.82 mg/l 4 hr Rat (NITE(2006))
- [Propylene glycol methyl ether acetate] : Steam LC50 = 28.8 mg/L/4 hr Rat (KOSHA)
- [4-Methyl-2-pentanone] : LC50 = 8.2 mg/l Rat (NITE)
- [Acetic acid ethyl ester] : Steam LC50 100 mg/l 4 hr Rat (LC50 = 200 mg/L/1hr conversion $\frac{1}{2}$)
- [Silicon dioxide] : LC50 > 2.2 mg/l 1 hr Rat (IUCLID)
- [Ethanol] : LC50 = 59.59 mg/L/4hr Rat (HSDB)
- [Secret] : LC50 = 72.6 mg/l 4 hr Rat (HSDB)
- [Secret] : LC50 83.9 mg/L/4 hr Rat
- [Secret] : dust LC50 \geq 0.477 mg/L 4 hr Rat (IUCLID)

o **Skin corrosion/irritation**

- Causes skin irritation

o **Serious eye damage/irritation**

- Causes serious eye irritation

o **Respiratory sensitization**

- Not available

o **Skin sensitization**

- Not available

o **Carcinogenicity**

*** IARC**

- [Cyclohexanone] : Group 3
- [Talc] : Group 2B
- [Titanium dioxide] : Group 2B
- [4-Methyl-2-pentanone] : Group 2B
- [Silicon dioxide] : Group 3
- [Ethanol] : Group 1
- [Secret] : Group 2B
- [Secret] : Group 3

*** OSHA**

- Not available

*** ACGIH**

- [Cyclohexanone] : A3
- [Talc] : A4
- [Titanium dioxide] : A4
- [4-Methyl-2-pentanone] : A3



- [Ethanol] : A3
- [Secret] : A3
- [Secret] : A4
- * **NTP**
 - Not available
- * **EU CLP**
 - [Solvent naphtha (petroleum), light arom.] : Carc. 1B
- **Germ cell mutagenicity**
 - Not available
- **Reproductive toxicity**
 - Not available
- **STOT-single exposure**
 - Causes damage to organs(Refer Section SDS 11)
 - May cause drowsiness and dizziness.
 - May cause respiratory irritation.
- **STOT-repeated exposure**
 - Not available
- **Aspiration hazard**
 - May be harmful if swallowed and enters airways

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- **Fish**
 - [Cyclohexanone] : LC50 = 527 mg/l 96 hr Pimephales promelas
 - [n-Butyl acetate] : LC50 = 62 mg/l 96 hr
 - [Talc] : LC50 > 100000 mg/l 24 hr Brachydanio rerio
 - [Solvent naphtha (petroleum), light arom.] : LC50 = 9.22 mg/l 96 hr Oncorhynchus mykiss
 - [Isobutyl acetate] : LC50 = 17 mg/l 96 hr
 - [Propylene glycol methyl ether acetate] : LC50 ≥ 100 mg/l 96 hr Oryzias latipes
 - [4-Methyl-2-pentanone] : LC50 = 540 mg/l 96 hr
 - [Acetic acid ethyl ester] : LC50 230 mg/l 96 hr Pimephales promelas
 - [Ethanol] : LC50 = 42 mg/l 96 hr Oncorhynchus mykiss
 - [Secret] : LC50 = 13400 mg/l 96 hr Oncorhynchus mykiss
 - [Secret] : LC50 > 100 mg/l 96 hr Other (Salmo trutta)
 - [Secret] : LC50 > 100 mg/l 96 hr
 - [Secret] : LC50 = 50 ~ 100 mg/l 96 hr Brachydanio rerio
 - [Secret] : LC50 = 87.095 mg/l 96 hr
 - [Secret] : LC50 15400 mg/l 96 hr Lepomis macrochirus
 - [Secret] : LC50 = 123.852 mg/l 96 hr
- **Crustaceans**
 - [Cyclohexanone] : EC50 = 820 mg/l 24 hr Daphnia magna
 - [Hexahydrobenzene] : EC50 = 0.9 mg/l 48 hr
 - [n-Butyl acetate] : LC50 = 32 mg/l 48 hr
 - [Talc] : LC50 = 94983.781 mg/l 48 hr
 - [Solvent naphtha (petroleum), light arom.] : EC50 = 6.14 mg/l 48 hr Daphnia magna
 - [Titanium dioxide] : EC50 > 1000 mg/l 48 hr
 - [Propylene glycol methyl ether acetate] : EC50 = 373 mg/l 48 hr Daphnia magna
 - [4-Methyl-2-pentanone] : EC50 = 170 mg/l 48 hr
 - [Acetic acid ethyl ester] : EC50 717 mg/l 48 hr Daphnia magna
 - [Ethanol] : EC50 = 2 mg/l 48 hr Daphnia magna
 - [Secret] : EC50 = 5600 mg/l 24 hr
 - [Secret] : EC50 = 3940 ~ 4670 mg/l 48 hr Daphnia magna



- [Secret] : EC50 > 100 mg/ℓ 48 hr Daphnia magna
- [Secret] : LC50 = 3317.276 mg/ℓ 48 hr
- [Secret] : LD50 > 100 mg/ℓ 96 hr Daphnia magna
- [Secret] : LC50 = 2332.935 mg/ℓ 48 hr

○ **Algae**

- [Cyclohexanone] : EC50 = 32.9 mg/ℓ 72 hr (Chlamydomonas reinhardtii(Algae))
- [Talc] : LC50 = 48545.539 mg/ℓ
- [Solvent naphtha (petroleum), light arom.] : EC50 = 19 mg/ℓ 72 hr Selenastrum capricornutum
- [Propylene glycol methyl ether acetate] : EC50 ≥ 1000 mg/ℓ 72 hr Selenastrum capricornutum
- [Acetic acid ethyl ester] : EC50 1800 ~ 3200 mg/ℓ 72 hr (Selenastrum sp.)
- [Secret] : EC50 > 100 mg/ℓ 72 hr Selenastrum capricornutum
- [Secret] : EC50 = 2.2 mg/ℓ 96 hr
- [Secret] : EC50 = 11.917 mg/ℓ 96 hr
- [Secret] : EC50 = 6.691 mg/ℓ 96 hr (No accurate information on Species)
- [Secret] : EC50 = 9.337 mg/ℓ 96 hr

B. Persistence and degradability

○ **Persistence**

- [Cyclohexanone] : log Kow = 0.81
- [n-Butyl acetate] : log Kow = 1.78
- [Talc] : log Kow = -1.50
- [Solvent naphtha (petroleum), light arom.] : log Kow = 2.1 ~ 6 (Estimates)
- [Isobutyl acetate] : log Kow = 1.78
- [Propylene glycol methyl ether acetate] : log Kow = 0.43
- [4-Methyl-2-pentanone] : log Kow = 1.38
- [Acetic acid ethyl ester] : log Kow 0.73
- [Silicon dioxide] : log Kow = 0.53
- [Secret] : log Kow = 0.62
- [Secret] : log Kow = 1.03
- [Secret] : log Kow = 0.35
- [Secret] : log Kow -0.77
- [Secret] : log Kow = 0.52

○ **Degradability**

- [Solvent naphtha (petroleum), light arom.] : BOD5/COD = 0.43
- [Acetic acid ethyl ester] : BOD5/COD 0.81
- [Ethanol] : BOD5/COD = 0.57

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [Cyclohexanone] : BCF = 2.4 (Estimates)
- [Hexahydrobenzene] : BCF = 129
- [Acetic acid ethyl ester] : BCF 30
- [Silicon dioxide] : BCF = 3.162
- [Secret] : BCF = 3.162
- [Secret] : BCF = 1.1
- [Secret] : BCF = 1.2

○ **Biodegradation**

- [Hexahydrobenzene] : Biodegradability = 77 (%) 28 day
- [n-Butyl acetate] : Biodegradability = 98 (%)
- [Propylene glycol methyl ether acetate] : Biodegradability > 60 (%) 28 day
- [Acetic acid ethyl ester] : 100 (%) 28 day
- [Ethanol] : Biodegradability = 75 (%) 20 day (Aerobic, Other, Easily decomposed)
- [Secret] : Biodegradability = 98 (%) 28 day



- [Secret] : (More than 95% decomposed after 3 days)

D. Mobility in soil

- [Ethanol] : Koc = 1
- [Secret] : Koc = 10.9
- [Secret] : Koc = 1.838

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- High temperature incinerate
- After taking off organic solvents that are supposed to be recycled, incinerate the rest of them at a high degree.

B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN number

- 1263

B. Proper shipping name

- PAINT INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS, VARNISH, POLISH, LIQUID FILLER, AND LIQUID LACQUER BASE

C. Hazard class

- 3

D. Packing group

- III

E. Marine pollutant

- Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

- POPs Management Law
 - Not applicable
- Information of EU Classification



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

*** Classification**

- [Cyclohexanone] : R10Xn; R20
- [Hexahydrobenzene] : F; R11Xn; R65Xi; R38R67N; R50-53
- [n-Butyl acetate] : R10 R66 R67
- [Solvent naphtha (petroleum), light arom.] : Carc. Cat. 2; R45/Muta. Cat. 2; R46, Xn; R65
- [Isobutyl acetate] : F; R11 R66
- [Propylene glycol methyl ether acetate] : R10
- [4-Methyl-2-pentanone] : F; R11 Xn; R20 Xi; R36/37 R66
- [Acetic acid ethyl ester] : F; R11 Xi; R36 R66 R67
- [Ethanol] : F; R11
- [Secret] : F; R11 Xi; R36 R67
- [Secret] : F; R11 T; R23/24/25-39/23/24/25
- [Secret] : R10 Repr. Cat. 2; R61 Xi; R37

*** Risk Phrases**

- [Cyclohexanone] : R10, R20
- [Hexahydrobenzene] : R11, R38, R65, R67, R50/53
- [n-Butyl acetate] : R10, R66, R67
- [Solvent naphtha (petroleum), light arom.] : R45, R65, R46
- [Isobutyl acetate] : R11, R66
- [Propylene glycol methyl ether acetate] : R10
- [4-Methyl-2-pentanone] : R11, R20, R36/37, R66
- [Acetic acid ethyl ester] : R11, R36, R66, R67
- [Ethanol] : R11
- [Secret] : R11, R36, R67
- [Secret] : R11, R23/24/25, R39/23/24/25
- [Secret] : R61, R10, R37

*** Safety Phrase**

- [Cyclohexanone] : S2, S25
- [Hexahydrobenzene] : S2, S9, S16, S25, S33, S51, S60, S61, S62
- [n-Butyl acetate] : S2, S25
- [Solvent naphtha (petroleum), light arom.] : S53, S45
- [Isobutyl acetate] : S2, S16, S23, S25, S29, S33
- [Propylene glycol methyl ether acetate] : S2
- [4-Methyl-2-pentanone] : S2, S9, S16, S29
- [Acetic acid ethyl ester] : S2, S16, S26, S33
- [Ethanol] : S2, S7, S16
- [Secret] : S2, S7, S16, S24/25, S26
- [Secret] : S1/2, S7, S16, S36/37, S45
- [Secret] : S53, S45

o **U.S. Federal regulations***** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- [Cyclohexanone] : 2267.995 kg 5000 lb
- [Hexahydrobenzene] : 453.599 kg 1000 lb
- [n-Butyl acetate] : 2267.995 kg 5000 lb
- [Isobutyl acetate] : 2267.995 kg 5000 lb
- [4-Methyl-2-pentanone] : 2267.995 kg 5000 lb
- [Acetic acid ethyl ester] : 2267.995 kg 5000 lb
- [Secret] : 2267.995 kg 5000 lb

*** EPCRA Section 302 (40CFR355.30)**

- Not applicable

*** EPCRA Section 304 (40CFR355.40)**

- Not applicable
- * **EPCRA Section 313 (40CFR372.65)**
 - [Hexahydrobenzene] : Applicable
 - [4-Methyl-2-pentanone] : Applicable
 - [Secret] : Applicable
- **Rotterdam Convention listed ingredients**
 - Not applicable
- **Stockholm Convention listed ingredients**
 - Not applicable
- **Montreal Protocol listed ingredients**
 - Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2016-09-02

C. Revision number and Last date revised

- 1 times, 2016-09-02

D. Other

- This MSDS is prepared according to the Globally Harmonized System (GHS).

