



Akzonobel Industrial Coatings Korea

# MATERIAL SAFETY DATA SHEET

## A/T#570(TX-F) THINNER(SLOW DRYING)

Date of issue: 2013-06-25

Revision date: 2014-03-12

Version: R0001.0003

### 1. IDENTIFICATION

#### A. Product name

- A/T#570(TX-F) THINNER(SLOW DRYING) [KF000034760]

#### B. Recommended use and restriction on use

- General use : Thinner
- Restriction on use : Do not use for other purposes

#### C. Manufacturer / Supplier / Distributor information

##### ○ Manufacturer information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 60, Bonsan 1-ro 56beon-gil, Jinyeong-eup, Gimhae-si, Gyeongsangnam-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 55-720-0200
- Fax number :
- E-mail address :

##### ○ Supplier/Distributor information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 11, Byeolmang-ro 459beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 31-490-4200
- Fax number :
- E-mail address :

### 2. HAZARD IDENTIFICATION

#### A. GHS Classification


- Acute toxicity (inhalation: vapor) : Category4
- Chronic aquatic toxicity : Category2
- Carcinogenicity : Category2
- Flammable liquids : Category3
- Specific target organ toxicity(Single exposure) : Category1
- Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)
- Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)
- Aspiration hazard : Category1

#### B. GHS label elements

##### ○ Hazard symbols



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



○ **Signal words**

- Danger

○ **Hazard statements**

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H332 Harmful if inhaled
- H335 May cause respiratory irritation.
- H336 May cause drowsiness and dizziness.
- H351 Suspected of causing cancer
- H370 Causes damage to organs(Refer Section SDS 11)
- H411 Toxic to aquatic life with long lasting effects

○ **Precautionary statements**

**1) Prevention**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

**2) Response**

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P307+P311 If exposed: Call a POISON CENTER or doctor/physician.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment
- P331 Do NOT induce vomiting.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).
- P391 Collect spillage.

**3) Storage**

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

**4) Disposal**

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

**C. Other hazards which do not result in classification : (NFPA Classification)**

- NFPA grade (0 ~ 4 level)



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Health : 0, Flammability : 3, Reactivity : 0

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
4-Methyl-2-pentanone	Methylisobutyl ketone, MIBK	108-10-1	20 ~ 30
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	20 ~ 30
2-Butoxyethanol acetate	Butyl cellosolve acetate	112-07-2	20 ~ 30
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	20 ~ 30
Solvent naphtha (petroleum), heavy arom.	Heavy aromatic naphtha	64742-94-5	20 ~ 30

### 4. FIRST AID MEASURES

#### A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

#### B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.

#### C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

#### D. Ingestion contact

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

#### E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

#### F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

### 5. FIREFIGHTING MEASURES

#### A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

#### B. Specific hazards arising from the chemical

- Not available

#### C. Special protective actions for firefighters



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Cool containers with water until well after fire is out.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- Avoid inhalation of materials or combustion by-products.
- Do not access if the tank on fire.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

## 6. ACCIDENTAL RELEASE MEASURES

### A. Personal precautions, protective equipment and emergency procedures

- Ventilate closed spaces before entering.
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Handling the damaged containers or spilled material after wearing protective equipment.
- Do not direct water at spill or source of leak.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

### B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

### C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.

## 7. HANDLING AND STORAGE

### A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Get the manual before use.
- Refer to Engineering controls and personal protective equipment.
- Dealing only with a well-ventilated place.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

### B. Conditions for safe storage, including any incompatibilities

- Save in cool, dry and well ventilated place.
- Check regularly for leaks.
- Do not use damaged containers.
- Do not apply direct heat.
- No open fire.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Store away from water and sewer.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### A. Exposure limits

- **ACGIH TLV**
  - [4-Methyl-2-pentanone] : TWA 50 ppm
  - [Isobutyl acetate] : TWA 150 ppm
  - [2-Butoxyethanol acetate] : TWA 20 ppm
  - [n-Butyl acetate] : TWA 150 ppm

### B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

### C. Personal protective equipment

- **Respiratory protection**
  - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
  - Respiratory protection is ranked in order from minimum to maximum.
  - Consider warning properties before use.
  - Any chemical cartridge respirator with organic vapor cartridge(s).
  - Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
  - Any air-purifying respirator with a full facepiece and an organic vapor canister.
  - For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- **Eye protection**
  - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
  - Provide an emergency eye wash station and quick drench shower in the immediate work area.
- **Hand protection**
  - Wear appropriate chemical resistant glove.
- **Skin protection**
  - Wear appropriate chemical resistant protective clothing.
- **Others**
  - Not available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	clear
B. Odor	Not available
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	110 °C
G. Flash point	30 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

N. Specific gravity	0.85~0.89
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	Not available

## 10. STABILITY AND REACTIVITY

### A. Chemical stability

- This material is stable under recommended storage and handling conditions.

### B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

### C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

### D. Incompatible materials

- Not available

### E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

## 11. TOXICOLOGICAL INFORMATION

### A. Information on the likely routes of exposure

- (Respiratory tracts)
  - May be fatal if swallowed and enters airways
  - May cause respiratory irritation.
- (Oral)
  - Not available
- (Eye·Skin)
  - Not available

### B. Delayed and immediate effects and also chronic effects from short and long term exposure

- Acute toxicity
  - \* Oral
    - [4-Methyl-2-pentanone] : LD50 = 2080 mg/kg Rat
    - [Isobutyl acetate] : LD50 = 15400 mg/kg Rat
    - [2-Butoxyethanol acetate] : LD50 = 2400 mg/kg Rat
    - [n-Butyl acetate] : LD50 = 14130 mg/kg Rat
    - [Solvent naphtha (petroleum), heavy arom.] : LD50 > 5000 mg/kg Rat
  - \* Dermal
    - [4-Methyl-2-pentanone] : LD50 = 3000 mg/kg rabbit
    - [Isobutyl acetate] : LD50 = 17400 mg/kg rabbit
    - [2-Butoxyethanol acetate] : LD50 = 1500 mg/kg rabbit
    - [n-Butyl acetate] : LD50 = 17600 mg/kg Rabbit
    - [Solvent naphtha (petroleum), heavy arom.] : LD50 > 2000 mg/kg Rabbit
  - \* Inhalation
    - [4-Methyl-2-pentanone] : LC50 = 8.2 mg/l Rat
    - [Isobutyl acetate] : LC50 = 8000 ppm 4 hr Rat



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [n-Butyl acetate] : Steam LC50 = 2000 ppm Rat
- [Solvent naphtha (petroleum), heavy arom.] : Mist LC50 > 0.59 mg/ℓ 4 hr Rat
- **Skin corrosion/irritation**
  - Not available
- **Serious eye damage/irritation**
  - Not available
- **Respiratory sensitization**
  - Not available
- **Skin sensitization**
  - Not available
- **Carcinogenicity**
  - \* **IARC**
    - [4-Methyl-2-pentanone] : 2B
  - \* **OSHA**
    - Not available
  - \* **ACGIH**
    - [4-Methyl-2-pentanone] : A3
    - [2-Butoxyethanol acetate] : A3
  - \* **NTP**
    - Not available
  - \* **EU CLP**
    - Not available
- **Germ cell mutagenicity**
  - Not available
- **Reproductive toxicity**
  - Not available
- **STOT-single exposure**
  - Causes damage to organs(Refer Section SDS 11)
  - May cause drowsiness and dizziness.
  - May cause respiratory irritation.
- **STOT-repeated exposure**
  - Not available
- **Aspiration hazard**
  - May be fatal if swallowed and enters airways

## 12. ECOLOGICAL INFORMATION

### A. Ecotoxicity

- **Fish**
  - [4-Methyl-2-pentanone] : LC50 = 540 mg/ℓ 96 hr
  - [Isobutyl acetate] : LC50 = 17 mg/ℓ 96 hr
  - [n-Butyl acetate] : LC50 = 62 mg/ℓ 96 hr
  - [Solvent naphtha (petroleum), heavy arom.] : LC50 = 45 mg/ℓ 96 hr Pimephales promelas
- **Crustaceans**
  - [4-Methyl-2-pentanone] : EC50 = 170 mg/ℓ 48 hr
  - [n-Butyl acetate] : LC50 = 32 mg/ℓ 48 hr
  - [Solvent naphtha (petroleum), heavy arom.] : EC50 = 0.95 mg/ℓ 48 hr Daphnia magna
- **Algae**
  - [Solvent naphtha (petroleum), heavy arom.] : EC50 = 2.5 mg/ℓ 72 hr Skeletonema costatum

### B. Persistence and degradability

- **Persistence**
  - [4-Methyl-2-pentanone] : log Kow = 1.38
  - [Isobutyl acetate] : log Kow = 1.78



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [n-Butyl acetate] : log Kow = 1.78
- [Solvent naphtha (petroleum), heavy arom.] : log Kow = 2.9 ~ 6.1

○ **Degradability**

- [2-Butoxyethanol acetate] : BOD5/COD = 0.51

### C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [2-Butoxyethanol acetate] : BCF = 3.2
- [Solvent naphtha (petroleum), heavy arom.] : BCF = 130 ~ 159

○ **Biodegradation**

- [2-Butoxyethanol acetate] : Biodegradability = 88 (%) 28 day (Aerobic, other bacteria: Belebtschlam, kommunal)
- [n-Butyl acetate] : Biodegradability = 98 (%)
- [Solvent naphtha (petroleum), heavy arom.] : Biodegradability = 39 (%) 28 day (Aerobic, Activated Sludge, Domestic wastewater, Does not decompose easily)

### D. Mobility in soil

- Not available

### E. Other adverse effects

- Not available

## 13. DISPOSAL CONSIDERATIONS

### A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat sepatatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- Will be pre-processed by the separation of oil and water.

### B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

## 14. TRANSPORT INFORMATION

### A. UN number

- 1263

### B. Proper shipping name

- Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

### C. Hazard class

- 3

### D. Packing group

- III

### E. Marine pollutant

- Not applicable

### F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



- Ems FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- Ems SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

## 15. REGULATORY INFORMATION

### A. National and/or international regulatory information

- **POPs Management Law**
  - Not applicable
- **Information of EU Classification**
  - \* **Classification**
    - [4-Methyl-2-pentanone] : F; R11 Xn; R20 Xi; R36/37 R66
    - [Isobutyl acetate] : F; R11 R66
    - [2-Butoxyethanol acetate] : Xn; R20/21
    - [n-Butyl acetate] : R10 R66 R67
    - [Solvent naphtha (petroleum), heavy arom.] : Xn; R65
  - \* **Risk Phrases**
    - [4-Methyl-2-pentanone] : R11, R20, R36/37, R66
    - [Isobutyl acetate] : R11, R66
    - [2-Butoxyethanol acetate] : R20/21
    - [n-Butyl acetate] : R10, R66, R67
    - [Solvent naphtha (petroleum), heavy arom.] : R65
  - \* **Safety Phrase**
    - [4-Methyl-2-pentanone] : S2, S9, S16, S29
    - [Isobutyl acetate] : S2, S16, S23, S25, S29, S33
    - [2-Butoxyethanol acetate] : S2, S24
    - [n-Butyl acetate] : S2, S25
    - [Solvent naphtha (petroleum), heavy arom.] : S2, S23, S24, S62
- **U.S. Federal regulations**
  - \* **OSHA PROCESS SAFETY (29CFR1910.119)**
    - Not applicable
  - \* **CERCLA Section 103 (40CFR302.4)**
    - [4-Methyl-2-pentanone] : 2267.995 kg 5000 lb
    - [Isobutyl acetate] : 2267.995 kg 5000 lb
    - [n-Butyl acetate] : 2267.995 kg 5000 lb
  - \* **EPCRA Section 302 (40CFR355.30)**
    - Not applicable
  - \* **EPCRA Section 304 (40CFR355.40)**
    - Not applicable
  - \* **EPCRA Section 313 (40CFR372.65)**
    - [4-Methyl-2-pentanone] : Applicable
- **Rotterdam Convention listed ingredients**
  - Not applicable
- **Stockholm Convention listed ingredients**
  - Not applicable
- **Montreal Protocol listed ingredients**
  - Not applicable

## 16. OTHER INFORMATION

### A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

**B. Issue date**

- 2013-06-25

**C. Revision number and Last date revised**

- 2 times, 2014-03-12

**D. Other**

- This MSDS is prepared according to the Globally Harmonized System (GHS).



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.