



Akzonobel Industrial Coatings Korea

MATERIAL SAFETY DATA SHEET

A/T#570-A THINNER

Date of issue: 2013-06-25

Revision date: 2015-06-17

Version: R0002.0001

1. IDENTIFICATION

A. Product name

- A/T#570-A THINNER [KF000033733]

B. Recommended use and restriction on use

- General use : Thinner
- Restriction on use : Do not use for other purposes

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 60, Bonsan 1-ro 56beon-gil, Jinyeong-eup, Gimhae-si, Gyeongsangnam-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 55-720-0200
- Fax number :
- E-mail address :

○ Supplier/Distributor information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 11, Byeolmang-ro 459beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 31-490-4200
- Fax number :
- E-mail address :

2. HAZARD IDENTIFICATION

A. GHS Classification

- Acute toxicity (dermal) : Category3
- Acute toxicity (inhalation: vapor) : Category3
- Carcinogenicity : Category2
- Reproductive toxicity : Category2
- Serious eye damage/irritation : Category2
- Flammable liquids : Category3
- Specific target organ toxicity(Single exposure) : Category1
- Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)
- Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)
- Specific target organ toxicity(Repeated exposure) : Category1
- Skin corrosion/irritation : Category2



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

B. GHS label elements

○ Hazard symbols



○ Signal words

- Danger

○ Hazard statements

- H226 Flammable liquid and vapour
- H311 Toxic in contact with skin
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H331 Toxic if inhaled
- H335 May cause respiratory irritation.
- H336 May cause drowsiness and dizziness.
- H351 Suspected of causing cancer
- H361 Suspected of damaging fertility or the unborn child
- H370 Causes damage to organs(Refer Section SDS 11)
- H372 Causes damage to organs through prolonged or repeated exposure (Refer Section SDS 11)

○ Precautionary statements

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

2) Response

- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P307+P311 If exposed: Call a POISON CENTER or doctor/physician.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P311 Call a POISON CENTER or doctor/physician.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment
- P322 Specific measures
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P361 Remove/Take off immediately all contaminated clothing.
- P362 Take off contaminated clothing and wash before reuse.



- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

o NFPA grade (0 ~ 4 level)

- Health : 2, Flammability : 3, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Toluene	Methylbenzene	108-88-3	30 ~ 40
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	30 ~ 40
2-Butoxyethanol	Ethylene glycol monobutyl ether	111-76-2	20 ~ 30
4-Heptanone, 2,6-dimethyl-	Heptan-4-one, 2,6-dimethyl-	108-83-8	1 ~ 10
4,6-Dimethylheptan-2-one	-	19549-80-5	1 ~ 10
Secret	Secret	-	0 ~ 1

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contact lenses if worn.

B. Skin contact

- Flush skin with plenty of wter for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Prevent the spread of the skin.
- Take the doctor's examination.
- Wash thoroughly after handling.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.
- Take the doctor's examination.

D. Ingestion contact

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES**A. Suitable (Unsuitable) extinguishing media**

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Cool containers with water until well after fire is out.
- Avoid inhalation of materials or combustion by-products.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

6. ACCIDENTAL RELEASE MEASURES**A. Personal precautions, protective equipment and emergency procedures**

- Ventilate closed spaces before entering.
- Must work against the wind, let the upwind people to evacuate.
- Do not touch spilled material. Stop leak if you can do it without risk.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.



7. HANDLING AND STORAGE

A. Precautions for safe handling

- Comply with all applicable laws and regulations for handling
- Get the manual before use.
- Dealing only with a well-ventilated place.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Keep in the original container.
- Please pay attention to incompatibilities materials and conditions to avoid.
- Keep sealed when not in use.
- No open fire.
- Prevent static electricity and keep away from combustible materials or heat sources.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- o **ACGIH TLV**
 - [Toluene] : TWA 20 ppm (75 mg/m³)
 - [Isobutyl acetate] : TWA, 150 ppm (713 mg/m³)
 - [2-Butoxyethanol] : TWA, 20 ppm (97 mg/m³)
 - [4-Heptanone, 2,6-dimethyl-] : TWA, 25 ppm (145 mg/m³)

B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Personal protective equipment

- o **Respiratory protection**
 - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
 - Respiratory protection is ranked in order from minimum to maximum.
 - Consider warning properties before use.
 - Any chemical cartridge respirator with organic vapor cartridge(s).
 - Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
 - Any air-purifying respirator with a full facepiece and an organic vapor canister.
 - For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- o **Eye protection**
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
- o **Hand protection**
 - Wear appropriate chemical resistant glove.
- o **Skin protection**
 - Wear appropriate chemical resistant protective clothing.
- o **Others**
 - Not available

9. PHYSICAL AND CHEMICAL PROPERTIES



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

A. Appearance	
- Appearance	Liquid
- Color	clear
B. Odor	Not available
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	110 °C
G. Flash point	23 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity(Relative density)	0.85~0.89
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY

A. Chemical Stability and Reactivity

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- (Respiratory tracts)
 - May cause respiratory irritation.
- (Oral)
 - Not available
- (Eye·Skin)
 - Causes serious eye irritation
 - Causes skin irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- **Acute toxicity**

- * **Oral**

- [Toluene] : rat LD50=2600 mg/kg
 - [Isobutyl acetate] : LD50 = 15400 mg/kg Rat
 - [2-Butoxyethanol] : LD50 = 1746 mg/kg Rat
 - [4-Heptanone, 2,6-dimethyl-] : LD50 > 5000 mg/kg Rat
 - [Secret] : LD50 = 3,560 mg/kg Rat

- * **Dermal**

- [Toluene] : rabbit LD50=12,000 mg/kg
 - [Isobutyl acetate] : LD50 = 17400 mg/kg rabbit
 - [2-Butoxyethanol] : LD50 = 99 mg/kg Rabbit
 - [4-Heptanone, 2,6-dimethyl-] : LD50 > 2000 mg/kg Rat
 - [Secret] : LD50 = 4,600 mg/kg Rabbit

- * **Inhalation**

- [Toluene] : rat LC50=28.1 mg/L/4hr
 - [Isobutyl acetate] : LC50 = 38.0 mg/L/4 hr Rat
 - [2-Butoxyethanol] : LC50 = 2.2 mg/l 4 hr Rat

- **Skin corrosion/irritation**

- Causes skin irritation

- **Serious eye damage/irritation**

- Causes serious eye irritation

- **Respiratory sensitization**

- Not available

- **Skin sensitization**

- Not available

- **Carcinogenicity**

- * **IARC**

- [Toluene] : Group 3
 - [2-Butoxyethanol] : Group 3

- * **OSHA**

- Not available

- * **ACGIH**

- [Toluene] : A4
 - [2-Butoxyethanol] : A3

- * **NTP**

- Not available

- * **EU CLP**

- Not available

- **Germ cell mutagenicity**

- Not available

- **Reproductive toxicity**

- Suspected of damaging fertility or the unborn child

- **STOT-single exposure**

- Causes damage to organs(Refer Section SDS 11)
 - May cause drowsiness and dizziness.
 - May cause respiratory irritation.

- **STOT-repeated exposure**

- Causes damage to organs through prolonged or repeated exposure (Refer Section SDS 11)

- **Aspiration hazard**

- Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- **Fish**
 - [Toluene] : LC50 24 mg/ℓ 96 hr Oncorhynchus mykiss
 - [Isobutyl acetate] : LC50 = 17 mg/ℓ 96 hr
 - [2-Butoxyethanol] : LC50 = 1250 mg/ℓ 96 hr
 - [4-Heptanone, 2,6-dimethyl-] : LC50 = 140 mg/ℓ 96 hr
 - [4,6-Dimethylheptan-2-one] : LC50 = 31.378 mg/ℓ 96 hr
 - [Secret] : LC50 = 12.568 mg/ℓ 96 hr (ECOSAR Class : Neutral Organics)
- **Crustaceans**
 - [Toluene] : EC50 11.5 mg/ℓ 48 hr Daphnia magna
 - [2-Butoxyethanol] : LC50 = 5.4 mg/ℓ 96 hr
 - [4-Heptanone, 2,6-dimethyl-] : LC50 = 65 mg/ℓ 24 hr
 - [4,6-Dimethylheptan-2-one] : LC50 = 34.949 mg/ℓ 48 hr
 - [Secret] : LC50 = 8.309 mg/ℓ 48 hr (ECOSAR Class : Neutral Organics)
- **Algae**
 - [4,6-Dimethylheptan-2-one] : EC50 = 22.565 mg/ℓ 96 hr
 - [Secret] : EC50 = 6.293 mg/ℓ 96 hr (ECOSAR Class : Neutral Organics)

B. Persistence and degradability

- **Persistence**
 - [Toluene] : log Kow 2.73
 - [Isobutyl acetate] : log Kow = 1.78
 - [2-Butoxyethanol] : log Kow = 0.83
 - [Secret] : log Kow = 3.08
- **Degradability**
 - Not available

C. Bioaccumulative potential

- **Bioaccumulative potential**
 - [4,6-Dimethylheptan-2-one] : BCF = 18.83
 - [Secret] : BCF = 50.02
- **Biodegradation**
 - [Toluene] : 86 (%) 20 day
 - [2-Butoxyethanol] : Biodegradability = 96 (%)

D. Mobility in soil

- [Secret] : Koc = 164.9

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- Will be pre-processed by the separation of oil and water.

B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.



14. TRANSPORT INFORMATION**A. UN number**

- 1263

B. Proper shipping name

- Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

C. Hazard class

- 3

D. Packing group

- III

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

15. REGULATORY INFORMATION**A. National and/or international regulatory information**

- **POPs Management Law**
 - Not applicable
- **Information of EU Classification**
 - * **Classification**
 - [Toluene] : F; R11 Repr.Cat.3; R63 Xn; R48/20-65 Xi; R38 R67
 - [Isobutyl acetate] : F; R11 R66
 - [2-Butoxyethanol] : Xn; R20/21/22 Xi; R36/38
 - [4-Heptanone, 2,6-dimethyl-] : R10 Xi; R37
 - * **Risk Phrases**
 - [Toluene] : R11, R38, R48/20, R63, R65, R67
 - [Isobutyl acetate] : R11, R66
 - [2-Butoxyethanol] : R20/21/22, R36/38
 - [4-Heptanone, 2,6-dimethyl-] : R10, R37
 - * **Safety Phrase**
 - [Toluene] : S2, S36/37, S46, S62
 - [Isobutyl acetate] : S2, S16, S23, S25, S29, S33
 - [2-Butoxyethanol] : S2, S36/37, S46
 - [4-Heptanone, 2,6-dimethyl-] : S2, S24
- **U.S. Federal regulations**
 - * **OSHA PROCESS SAFETY (29CFR1910.119)**
 - Not applicable
 - * **CERCLA Section 103 (40CFR302.4)**
 - [Toluene] : 453.599 kg 1000 lb
 - [Isobutyl acetate] : 2267.995 kg 5000 lb
 - * **EPCRA Section 302 (40CFR355.30)**
 - Not applicable
 - * **EPCRA Section 304 (40CFR355.40)**
 - Not applicable
 - * **EPCRA Section 313 (40CFR372.65)**



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Toluene] : Applicable
- **Rotterdam Convention listed ingredients**
 - Not applicable
- **Stockholm Convention listed ingredients**
 - Not applicable
- **Montreal Protocol listed ingredients**
 - Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2013-06-25

C. Revision number and Last date revised

- 2 times, 2015-06-17

D. Other

- This MSDS is prepared according to the Globally Harmonized System (GHS).

