



Akzonobel Industrial Coatings Korea

MATERIAL SAFETY DATA SHEET

RESOTHANE-HT#200(TX-F) GA3

Date of issue: 2013-06-26

Revision date: 2014-03-11

Version: R0001.0002

1. IDENTIFICATION

A. Product name

- RESOTHANE-HT#200(TX-F) GA3 [KF000033736]

B. Recommended use and restriction on use

- General use : paint applid on plastic resin
- Restriction on use : Do not use for other purposes

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 60, Bonsan 1-ro 56beon-gil, Jinyeong-eup, Gimhae-si, Gyeongsangnam-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 55-720-0200
- Fax number :
- E-mail address :

○ Supplier/Distributor information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 11, Byeolmang-ro 459beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 31-490-4200
- Fax number :
- E-mail address :

2. HAZARD IDENTIFICATION

A. GHS Classification

- Acute toxicity (inhalation: vapor) : Category4
- Carcinogenicity : Category1B
- Germ cell mutagenicity : Category1B
- Flammable liquids : Category3
- Specific target organ toxicity(Single exposure) : Category1
- Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)

B. GHS label elements

- Hazard symbols



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



○ **Signal words**

- Danger

○ **Hazard statements**

- H226 Flammable liquid and vapour
- H332 Harmful if inhaled
- H335 May cause respiratory irritation.
- H340 May cause genetic defects
- H350 May cause cancer
- H370 Causes damage to organs(Refer Section SDS 11)

○ **Precautionary statements**

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

2) Response

- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P307+P311 If exposed: Call a POISON CENTER or doctor/physician.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

○ **NFPA grade (0 ~ 4 level)**

- Health : 0, Flammability : 3, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	30 ~ 40



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

Acryl resin	-	-	20 ~ 30
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	1 ~ 10
4-Methyl-2-pentanone	Methylisobutyl ketone, MIBK	108-10-1	1 ~ 10
Titanium dioxide	Titanium oxide (TiO ₂)	13463-67-7	1 ~ 10
Acetic acid ethyl ester	Ethyl acetate	141-78-6	1 ~ 10
Methyl Ethyl Ketone	2-Butanone	78-93-3	1 ~ 10
Silicon dioxide	Precipitated silica	112926-00-8	1 ~ 10
Cellulose acetate butylate	Cellulose, acetate butanoate	9004-36-8	1 ~ 10
C.I. pigment yellow 042	FERRIC OXIDE, FERRIC HYDROXIDE, CALCIUM CARBONATE	51274-00-1	1 ~ 10
Naphtha (petroleum), hydrotreated heavy	Naphtha	64742-48-9	0 ~ 1
Ethanol	Alcohol anhydrous	64-17-5	0 ~ 1
Secret	Secret	-	1 ~ 10

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Remove contaminated clothing, shoes and isolate.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Cool containers with water until well after fire is out.
- Keep unauthorized personnel out.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- Avoid inhalation of materials or combustion by-products.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

6. ACCIDENTAL RELEASE MEASURES**A. Personal precautions, protective equipment and emergency procedures**

- Wear proper personal protective apparatus as indicated in Section 8 and avoid skin contact and inhalation.
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.
- Spilled material should be treated as a potential risk of waste collected.

7. HANDLING AND STORAGE**A. Precautions for safe handling**

- Avoid contact with incompatible materials.
- Get the manual before use.
- Do not handle until all safety precautions have been read and understood.
- Operators should wear antistatic footwear and clothing.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Do not use damaged containers.
- Do not apply direct heat.
- Keep sealed when not in use.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- No open fire.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- **ACGIH TLV**
 - [n-Butyl acetate] : TWA 150 ppm
 - [Isobutyl acetate] : TWA 150 ppm
 - [4-Methyl-2-pentanone] : TWA 50 ppm
 - [Titanium dioxide] : TWA 10 mg/m³
 - [Acetic acid ethyl ester] : TWA 400 ppm
 - [Methyl Ethyl Ketone] : TWA 200 ppm
 - [C.I. pigment yellow 042] : TWA : 5 mg/m³ Iron oxides(fume)
 - [Secret] : TWA 3.5 mg/m³
 - [Secret] : TWA : 5 mg/m³ (fume)
 - [Ethanol] : TWA 1000 ppm

B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Personal protective equipment

- **Respiratory protection**
 - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
 - Respiratory protection is ranked in order from minimum to maximum.
 - Consider warning properties before use.
 - Any chemical cartridge respirator with organic vapor cartridge(s).
 - Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
 - Any air-purifying respirator with a full facepiece and an organic vapor canister.
 - For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- **Eye protection**
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
- **Hand protection**
 - Wear appropriate chemical resistant glove.
- **Skin protection**
 - Wear appropriate chemical resistant protective clothing.
- **Others**
 - Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(Viscous liquid)
- Color	GRAY
B. Odor	Not available
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

F. Initial Boiling Point/Boiling Ranges	79 °C
G. Flash point	23 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity	0.97~1.03
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	420 °C
Q. Decomposition temperature	Not available
R. Viscosity	65~71 KU
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY

A. Chemical stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- (Respiratory tracts)
 - May cause respiratory irritation.
- (Oral)
 - Not available
- (Eye·Skin)
 - Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- Acute toxicity
 - * Oral
 - [n-Butyl acetate] : LD50 = 14130 mg/kg Rat
 - [Isobutyl acetate] : LD50 = 15400 mg/kg Rat
 - [4-Methyl-2-pentanone] : LD50 = 2080 mg/kg Rat
 - [Titanium dioxide] : LD50 > 10000 mg/kg Rat
 - [Acetic acid ethyl ester] : LD50 5620 mg/kg Rat
 - [Methyl Ethyl Ketone] : LD50 2737 mg/kg Rat
 - [Silicon dioxide] : LD50 = 3300 mg/kg (Species : not available)



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Secret] : LD50 > 5000 mg/kg Rat
- [Naphtha (petroleum), hydrotreated heavy] : LD50 > 15000 mg/kg Rat
- [Secret] : LD50 = 15400 mg/kg Rat
- [Secret] : LD50 = 3160 mg/kg Rat
- [Secret] : LD50 = 7725 mg/kg Rat (Oral)
- [Secret] : LD50 > 10000 mg/kg Rat
- [Ethanol] : LD50 = 6200 mg/kg Rat
- [Secret] : LD50 = 5000 mg/kg Rat
- [Secret] : LD50 = 2369 mg/kg Rat
- [Secret] : LD50 = 600 mg/kg Rat
- [Secret] : LD50 = 526 mg/kg Rat

*** Dermal**

- [n-Butyl acetate] : LD50 = 17600 mg/kg Rabbit
- [Isobutyl acetate] : LD50 = 17400 mg/kg rabbit
- [4-Methyl-2-pentanone] : LD50 = 3000 mg/kg rabbit
- [Titanium dioxide] : LD50 > 10000 mg/kg Rabbit
- [Acetic acid ethyl ester] : LD50 > 18000 mg/kg Rabbit
- [Methyl Ethyl Ketone] : LD50 6480 mg/kg rabbit
- [Silicon dioxide] : LD50 = 5000 mg/kg
- [Naphtha (petroleum), hydrotreated heavy] : LD50 > 3160 mg/kg Rabbit
- [Secret] : LD50 = 3000 mg/kg rabbit
- [Secret] : LD50 = 5000 mg/kg Rat
- [Secret] : LD50 = 1488 mg/kg rabbit
- [Secret] : LD50 > 2000 mg/kg Rabbit

*** Inhalation**

- [n-Butyl acetate] : Steam LC50 = 2000 ppm Rat
- [Isobutyl acetate] : LC50 = 8000 ppm 4 hr Rat
- [4-Methyl-2-pentanone] : LC50 = 8.2 mg/l Rat
- [Titanium dioxide] : LC50 > 6.82 mg/l 4 hr Rat
- [Acetic acid ethyl ester] : Steam LC50 100 mg/l 4 hr Rat (LC50 = 200 mg/L/1hr conversion $\frac{1}{60}$)
- [Methyl Ethyl Ketone] : Steam LC50 32 mg/l 4 hr Mouse
- [Silicon dioxide] : Steam LC50 > 2.0 mg/l Rat
- [Secret] : dust LC50 \geq 0.477 mg/kg 4 hr Rat
- [Ethanol] : LC50 = 20000 ppm 10 hr Rat
- [Secret] : Steam LC50 8050 ppm 4 hr Rat

○ **Skin corrosion/irritation**

- Not available

○ **Serious eye damage/irritation**

- Not available

○ **Respiratory sensitization**

- Not available

○ **Skin sensitization**

- Not available

○ **Carcinogenicity**

*** IARC**

- [4-Methyl-2-pentanone] : 2B
- [Titanium dioxide] : 2B
- [Silicon dioxide] : Group 3 (Silica, amorphous)
- [Secret] : 2B
- [Secret] : 3
- [Secret] : Group 3
- [Ethanol] : 1

*** OSHA**



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Not available

*** ACGIH**

- [4-Methyl-2-pentanone] : A3

- [Titanium dioxide] : A4

- [Secret] : A4

- [Ethanol] : A3

*** NTP**

- Not available

*** EU CLP**

- [Naphtha (petroleum), hydrotreated heavy] : Carc. 1B

○ **Germ cell mutagenicity**

- May cause genetic defects

○ **Reproductive toxicity**

- Not available

○ **STOT-single exposure**

- Causes damage to organs(Refer Section SDS 11)

- May cause respiratory irritation.

○ **STOT-repeated exposure**

- Not available

○ **Aspiration hazard**

- Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

○ **Fish**

- [n-Butyl acetate] : LC50 = 62 mg/l 96 hr

- [Isobutyl acetate] : LC50 = 17 mg/l 96 hr

- [4-Methyl-2-pentanone] : LC50 = 540 mg/l 96 hr

- [Acetic acid ethyl ester] : LC50 230 mg/l 96 hr Pimephales promelas

- [Methyl Ethyl Ketone] : LC50 3220 mg/l 96 hr Pimephales promelas

- [Naphtha (petroleum), hydrotreated heavy] : LC50 = 2200 mg/l 96 hr Pimephales promelas

- [Secret] : LC50 = 832 mg/l 96 hr

- [Secret] : LC50 > 100 mg/l 96 hr Other (Salmo trutta)

- [Ethanol] : LC50 = 42 mg/l 96 hr Oncorhynchus mykiss

- [Secret] : LC50 = 0.97 mg/l 96 hr Lepomis macrochirus

- [Secret] : LC50 > 20000 mg/l 96 hr Oncorhynchus mykiss

- [Secret] : LC50 = 0.996 mg/l 96 hr

- [Secret] : LC50 = 315 mg/l 96 hr Fundulus heteroclitus

- [Secret] : LC50 4.8 mg/l 96 hr Brachydanio rerio

○ **Crustaceans**

- [n-Butyl acetate] : LC50 = 32 mg/l 48 hr

- [4-Methyl-2-pentanone] : EC50 = 170 mg/l 48 hr

- [Titanium dioxide] : EC50 > 1000 mg/l 48 hr

- [Acetic acid ethyl ester] : EC50 717 mg/l 48 hr Daphnia magna

- [Methyl Ethyl Ketone] : EC50 5091 mg/l 48 hr Daphnia magna

- [Naphtha (petroleum), hydrotreated heavy] : LC50 = 2.6 mg/l 96 hr (Species: Chaetogammarus marinus)

- [Secret] : EC50 = 5600 mg/l 24 hr

- [Secret] : LC50 = 1.23 mg/l 48 hr

- [Secret] : EC50 > 100 mg/l 48 hr Daphnia magna

- [Ethanol] : EC50 = 2 mg/l 48 hr Daphnia magna

- [Secret] : EC50 = 20 mg/l 24 hr

- [Secret] : LC50 = 0.110 mg/l 48 hr



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Secret] : EC50 = 1.2 mg/ℓ 64 hr *Daphnia magna*
- [Secret] : EC50 \geq 3.2 mg/ℓ 48 hr *Daphnia magna*

○ **Algae**

- [Acetic acid ethyl ester] : EC50 1800 ~ 3200 mg/ℓ 72 hr (*Selenastrum* sp.)
- [Methyl Ethyl Ketone] : EC50 > 500 mg/ℓ 96 hr *Skeletonema costatum*
- [Secret] : EC50 > 500 mg/ℓ 72 hr
- [Secret] : EC50 > 100 mg/ℓ 72 hr *Selenastrum capricornutum*
- [Secret] : EC50 = 0.017 mg/ℓ 96 hr
- [Secret] : EC50 = 0.615 mg/ℓ 96 hr

B. Persistence and degradability

○ **Persistence**

- [n-Butyl acetate] : log Kow = 1.78
- [Isobutyl acetate] : log Kow = 1.78
- [4-Methyl-2-pentanone] : log Kow = 1.38
- [Acetic acid ethyl ester] : log Kow 0.73
- [Methyl Ethyl Ketone] : log Kow 0.29
- [Naphtha (petroleum), hydrotreated heavy] : log Kow = 2.1 ~ 6 (Estimates)
- [Secret] : log Kow = 0.53
- [Secret] : log Kow = -0.54
- [Secret] : log Kow = 0.97 (Estimates)
- [Secret] : log Kow = 0.37 (at 25 °C)
- [Secret] : log Kow = 5.14
- [Secret] : log Kow = -2.7
- [Secret] : log Kow 4.57

○ **Degradability**

- [Acetic acid ethyl ester] : BOD5/COD 0.81
- [Secret] : BOD5/COD = 0.68
- [Ethanol] : BOD5/COD = 0.57

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [Acetic acid ethyl ester] : BCF 30
- [Secret] : BCF = 3.162
- [Secret] : BCF = 0.16
- [Secret] : BCF = 1351
- [Secret] : BCF = 180.1

○ **Biodegradation**

- [n-Butyl acetate] : Biodegradability = 98 (%)
- [Acetic acid ethyl ester] : 100 (%) 28 day
- [Methyl Ethyl Ketone] : 89 (%) 20 day
- [Naphtha (petroleum), hydrotreated heavy] : Biodegradability = 10 (%) 28 day (Aerobic, Activated Sludge, Domestic wastewater, Does not decompose easily)
- [Secret] : Biodegradability = 73 (%) 28 day
- [Ethanol] : Biodegradability = 75 (%) 20 day (Aerobic, Other, Easily decomposed)
- [Secret] : Biodegradability = 38 (%) 28 day
- [Secret] : 41 ~ 42 (%) 28 day

D. Mobility in soil

- [Ethanol] : Koc = 1

E. Other adverse effects

- Not available



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- High temperature incinerate
- After taking off organic solvents that are supposed to be recycled, incinerate the rest of them at a high degree.

B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN number

- 1263

B. Proper shipping name

- Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

C. Hazard class

- 3

D. Packing group

- III

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

o POPs Management Law

- Not applicable

o Information of EU Classification

* Classification

- [n-Butyl acetate] : R10 R66 R67
- [Isobutyl acetate] : F; R11 R66
- [4-Methyl-2-pentanone] : F; R11 Xn; R20 Xi; R36/37 R66
- [Acetic acid ethyl ester] : F; R11 Xi; R36 R66 R67
- [Methyl Ethyl Ketone] : F; R11 Xi; R36 R66 R67
- [Naphtha (petroleum), hydrotreated heavy] : Carc. Cat. 2; R45/Muta. Cat. 2; R46, Xn; R65
- [Secret] : Repr. Cat. 2; R61, Xi; R36/37/38
- [Ethanol] : F; R11

* Risk Phrases

- [n-Butyl acetate] : R10, R66, R67



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Isobutyl acetate] : R11, R66
- [4-Methyl-2-pentanone] : R11, R20, R36/37, R66
- [Acetic acid ethyl ester] : R11, R36, R66, R67
- [Methyl Ethyl Ketone] : R11, R36, R66, R67
- [Naphtha (petroleum), hydrotreated heavy] : R45, R65, R46
- [Secret] : R61, R36/37/38
- [Ethanol] : R11

*** Safety Phrase**

- [n-Butyl acetate] : S2, S25
- [Isobutyl acetate] : S2, S16, S23, S25, S29, S33
- [4-Methyl-2-pentanone] : S2, S9, S16, S29
- [Acetic acid ethyl ester] : S2, S16, S26, S33
- [Methyl Ethyl Ketone] : S2, S9, S16
- [Naphtha (petroleum), hydrotreated heavy] : S53, S45
- [Secret] : S53, S45
- [Ethanol] : S2, S7, S16

○ **U.S. Federal regulations**

*** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- [n-Butyl acetate] : 2267.995 kg 5000 lb
- [Isobutyl acetate] : 2267.995 kg 5000 lb
- [4-Methyl-2-pentanone] : 2267.995 kg 5000 lb
- [Acetic acid ethyl ester] : 2267.995 kg 5000 lb
- [Methyl Ethyl Ketone] : 2267.995 kg 5000 lb

*** EPCRA Section 302 (40CFR355.30)**

- Not applicable

*** EPCRA Section 304 (40CFR355.40)**

- Not applicable

*** EPCRA Section 313 (40CFR372.65)**

- [4-Methyl-2-pentanone] : Applicable
- [Secret] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2013-06-26

C. Revision number and Last date revised

- 1 times, 2014-03-11

D. Other



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- This MSDS is prepared according to the Globally Harmonized System (GHS).



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.