



Akzonobel Industrial Coatings Korea

MATERIAL SAFETY DATA SHEET

TAN TAN CLEAR 2(AUTO)

Date of issue: 2013-06-26

Revision date: Not applicable

Version: R0001.0001

1. IDENTIFICATION

A. Product name

- TAN TAN CLEAR 2(AUTO) [KF000031906]

B. Recommended use and restriction on use

- General use : paint applid on plastic resin
- Restriction on use : Do not use for other purposes

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 60, Bonsan 1-ro 56beon-gil, Jinyeong-eup, Gimhae-si, Gyeongsangnam-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 55-720-0200
- Fax number :
- E-mail address :

○ Supplier/Distributor information

- Company name : Akzonobel Industrial Coatings Korea Ltd.
- Address : 11, Byeolmang-ro 459beon-gil, Danwon-gu, Ansan-si, Gyeonggi-do, Korea
- Dept. :
- Telephone number :
- Emergency telephone number : (82) 31-490-4200
- Fax number :
- E-mail address :

2. HAZARD IDENTIFICATION

A. GHS Classification


- Acute toxicity (inhalation: vapor) : Category4
- Chronic aquatic toxicity : Category2
- Carcinogenicity : Category1B
- Reproductive toxicity : Category1A
- Serious eye damage/irritation : Category2
- Flammable liquids : Category2
- Specific target organ toxicity(Single exposure) : Category2
- Skin corrosion/irritation : Category2
- Aspiration hazard : Category2

B. GHS label elements

○ Hazard symbols



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



○ **Signal words**

- Danger

○ **Hazard statements**

- H225 Highly flammable liquid and vapour
- H305 May be harmful if swallowed and enters airways
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H350 May cause cancer
- H360 May damage fertility or the unborn child
- H371 May cause damage to organs (Refer Section SDS 11)
- H411 Toxic to aquatic life with long lasting effects

○ **Precautionary statements**

1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P309+P311 If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment
- P331 Do NOT induce vomiting.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).
- P391 Collect spillage.

3) Storage

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

o **NFPA grade (0 ~ 4 level)**

- Health : 2, Flammability : 0, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Linseed oil, polymer with glycerol and phthalic anhydride	-	66070-59-5	40 ~ 50
Xylene	Dimethylbenzene	1330-20-7	30 ~ 40
Propylene glycol methyl ether acetate	Propylene glycol monomethyl ether acetate	108-65-6	1 ~ 10
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	1 ~ 10
Solvent naphtha (petroleum), light arom.	Naphtha	64742-95-6	1 ~ 10
Ethylbenzene	Benzene, ethyl-	100-41-4	0 ~ 1
Toluene	Methylbenzene	108-88-3	0 ~ 1
Secret	Secret	-	1 ~ 10

4. FIRST AID MEASURES**A. Eye contact**

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms (flare, irritate) occur.
- Remove contact lenses if worn.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms (flare, irritate) occur.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

D. Ingestion contact

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES**A. Suitable (Unsuitable) extinguishing media**

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Keep unauthorized personnel out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

6. ACCIDENTAL RELEASE MEASURES**A. Personal precautions, protective equipment and emergency procedures**

- Wear proper personal protective apparatus as indicated in Section 8 and avoid skin contact and inhalation.
- Ventilate closed spaces before entering.
- Move container to safe area from the leak area.
- Handling the damaged containers or spilled material after wearing protective equipment.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.
- Spilled material should be treated as a potential risk of waste collected.

7. HANDLING AND STORAGE**A. Precautions for safe handling**

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Wash thoroughly after handling.
- Avoid contact with incompatible materials.
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

B. Conditions for safe storage, including any incompatibilities

- Check regularly for leaks.
- Do not apply direct heat.
- Save applicable laws and regulations.
- No open fire.
- Prevent static electricity and keep away from combustible materials or heat sources.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- o **ACGIH TLV**
 - [Linseed oil, polymer with glycerol and phthalic anhydride] : Not available
 - [Xylene] : TWA 100 ppm
 - [n-Butyl acetate] : TWA 150 ppm
 - [Secret] : TWA 25 ppm
 - [Ethylbenzene] : TWA 100 ppm
 - [Toluene] : TWA 50 ppm
 - [Secret] : TWA 100 ppm

B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Personal protective equipment

- o **Respiratory protection**
 - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
 - Respiratory protection is ranked in order from minimum to maximum.
 - Consider warning properties before use.
 - Any chemical cartridge respirator with organic vapor cartridge(s).
 - Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
 - Any air-purifying respirator with a full facepiece and an organic vapor canister.
 - For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- o **Eye protection**
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
- o **Hand protection**
 - Wear appropriate chemical resistant glove.
- o **Skin protection**
 - Wear appropriate chemical resistant protective clothing.
- o **Others**
 - Not available



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(Viscous liquid)
- Color	clear
B. Odor	Not available
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	100 °C
G. Flash point	21 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity	0.90~1.00
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	Not available
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY

A. Chemical stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- (Respiratory tracts)
 - May be harmful if swallowed and enters airways
- (Oral)
 - Not available
- (Eye·Skin)
 - Causes serious eye irritation



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Causes skin irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure

○ Acute toxicity

* Oral

- [Xylene] : LD50 3500 mg/kg Rat
- [Propylene glycol methyl ether acetate] : LD50 = 8532 mg/kg Rat
- [n-Butyl acetate] : LD50 = 14130 mg/kg Rat
- [Solvent naphtha (petroleum), light arom.] : LD50 = 8400 mg/kg Rat
- [Secret] : LD50 > 5000 mg/kg Rat
- [Ethylbenzene] : LD50 = 3500 mg/kg Rat
- [Toluene] : LD50 2600 mg/kg Rat
- [Secret] : LD50 > 2000 mg/kg Rat
- [Secret] : LD50 = 4250 mg/kg Rat
- [Secret] : LD50 = 5660 mg/kg Rat
- [Secret] : LD50 > 17000 mg/kg Rat

* Dermal

- [Xylene] : LD50 4350 mg/kg Rabbit
- [Propylene glycol methyl ether acetate] : LD50 > 5000 mg/kg Rabbit
- [n-Butyl acetate] : LD50 = 17600 mg/kg Rabbit
- [Solvent naphtha (petroleum), light arom.] : LD50 > 2000 mg/kg Rabbit
- [Secret] : LD50 > 2000 mg/kg Rat
- [Ethylbenzene] : LD50 = 15400 mg/kg Rabbit
- [Toluene] : LD50 120000 mg/kg Rat
- [Secret] : LD50 2000 mg/kg Rabbit
- [Secret] : LD50 = 13000 mg/kg Rabbit
- [Secret] : LD50 > 5000 mg/kg Rabbit
- [Secret] : LD50 = 2700 mg/kg Rabbit
- [Secret] : LD50 > 2000 mg/kg Rabbit

* Inhalation

- [Xylene] : Steam LC50 6700 ppm 4 hr Rat (Equivalents : 29.09 mg/L)
- [Propylene glycol methyl ether acetate] : Steam LC50 = 4345 ppm 6 hr Rat
- [n-Butyl acetate] : Steam LC50 = 2000 ppm Rat
- [Solvent naphtha (petroleum), light arom.] : Mist LC50 = 3400 ppm 4 hr Rat
- [Ethylbenzene] : Steam LC50 = 4000 ppm 4 hr Rat (Equivalents : 17.4 mg/L)
- [Toluene] : LC50 12.5 mg/ℓ 4 hr Rat
- [Secret] : Mist LC50 2.18 mg/ℓ 4 hr Rat
- [Secret] : LC50 = 6 mg/ℓ 4 hr Rat

○ Skin corrosion/irritation

- Causes skin irritation

○ Serious eye damage/irritation

- Causes serious eye irritation

○ Respiratory sensitization

- Not available

○ Skin sensitization

- Not available

○ Carcinogenicity

* IARC

- [Ethylbenzene] : Group 2B

* OSHA

- Not available

* ACGIH

- [Ethylbenzene] : A3

* NTP



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- Not available

*** EU CLP**

- [Solvent naphtha (petroleum), light arom.] : Carc. 1B

- [Secret] : Carc. 1B (Except when less than 3% DMSO extract as measured by the IP346 method.)

○ **Germ cell mutagenicity**

- Not available

○ **Reproductive toxicity**

- May damage fertility or the unborn child

○ **STOT-single exposure**

- May cause damage to organs (Refer Section SDS 11)

○ **STOT-repeated exposure**

- Not available

○ **Aspiration hazard**

- May be harmful if swallowed and enters airways

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

○ **Fish**

- [Xylene] : LC50 3.3 mg/ℓ 96 hr

- [Propylene glycol methyl ether acetate] : LC50 ≥ 100 mg/ℓ 96 hr *Oryzias latipes*

- [n-Butyl acetate] : LC50 = 62 mg/ℓ 96 hr

- [Solvent naphtha (petroleum), light arom.] : LC50 = 9.22 mg/ℓ 96 hr *Oncorhynchus mykiss*

- [Secret] : LC50 = 140 mg/ℓ 96 hr

- [Ethylbenzene] : LC50 = 9.09 mg/ℓ 96 hr

- [Toluene] : LC50 24 mg/ℓ 96 hr *Oncorhynchus mykiss*

- [Secret] : LC50 > 5000 mg/ℓ 96 hr *Oncorhynchus mykiss*

- [Secret] : LC50 = 31.378 mg/ℓ 96 hr

- [Secret] : LC50 = 320 mg/ℓ 96 hr (*Danio rerio*)

- [Secret] : LC50 = 123.852 mg/ℓ 96 hr

- [Secret] : LC50 = 1300 mg/ℓ 96 hr

- [Secret] : LC50 = 37.79 mg/ℓ 96 hr *Lepomis macrochirus*

○ **Crustaceans**

- [Xylene] : LC50 190 mg/ℓ 96 hr

- [Propylene glycol methyl ether acetate] : EC50 = 373 mg/ℓ 48 hr *Daphnia magna*

- [n-Butyl acetate] : LC50 = 32 mg/ℓ 48 hr

- [Solvent naphtha (petroleum), light arom.] : EC50 = 6.14 mg/ℓ 48 hr *Daphnia magna*

- [Secret] : LC50 = 65 mg/ℓ 24 hr

- [Ethylbenzene] : LC50 = 0.4 mg/ℓ 96 hr

- [Toluene] : EC50 11.5 mg/ℓ 48 hr *Daphnia magna*

- [Secret] : EC50 > 1000 mg/ℓ 48 hr *Daphnia magna*

- [Secret] : EC50 > 500 mg/ℓ 48 hr

- [Secret] : LC50 = 34.949 mg/ℓ 48 hr

- [Secret] : EC50 = 560 mg/ℓ 48 hr *Daphnia magna*

- [Secret] : EC50 = 280 mg/ℓ 24 hr *Daphnia magna*

- [Secret] : LC50 = 2332.935 mg/ℓ 48 hr

- [Secret] : LC50 = 44.5 mg/ℓ 48 hr *Daphnia magna*

○ **Algae**

- [Propylene glycol methyl ether acetate] : EC50 ≥ 1000 mg/ℓ 72 hr *Selenastrum capricornutum*

- [Solvent naphtha (petroleum), light arom.] : EC50 = 19 mg/ℓ 72 hr *Selenastrum capricornutum*

- [Secret] : EC50 > 1000 mg/ℓ 96 hr *Scenedesmus subspicatus*

- [Secret] : EC50 = 22.565 mg/ℓ 96 hr

- [Secret] : EC50 = 11.038 mg/ℓ 96 hr



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Secret] : EC50 = 9.337 mg/l 96 hr

B. Persistence and degradability

○ Persistence

- [Propylene glycol methyl ether acetate] : log Kow = 0.43
- [n-Butyl acetate] : log Kow = 1.78
- [Solvent naphtha (petroleum), light arom.] : log Kow = 2.1 ~ 6 (Estimates)
- [Toluene] : log Kow 2.73
- [Secret] : log Kow 3.9 ~ 6 (Estimates)
- [Secret] : log Kow = -0.18
- [Secret] : log Kow = 1.057
- [Secret] : log Kow = 0.52

○ Degradability

- [Solvent naphtha (petroleum), light arom.] : BOD5/COD = 0.43
- [Secret] : BOD5/COD = 0.12

C. Bioaccumulative potential

○ Bioaccumulative potential

- [Secret] : BCF = 2
- [Secret] : BCF = 18.83
- [Secret] : BCF = 3
- [Secret] : BCF = 3.162

○ Biodegradation

- [Xylene] : 39 (%)
- [Propylene glycol methyl ether acetate] : Biodegradability > 60 (%) 28 day
- [n-Butyl acetate] : Biodegradability = 98 (%)
- [Toluene] : 86 (%) 20 day
- [Secret] : 6 (%) 28 day (Aerobic, Domestic wastewater, does not decompose easily)
- [Secret] : Biodegradability = 90 (%) 29 day (Aerobic, industrial sewage, Easily decomposed)
- [Secret] : Biodegradability > 90 (%) 5 day
- [Secret] : Biodegradability = 58 (%) 28 day (Aerobic, Activated Sludge, Easily decomposed)

D. Mobility in soil

- [Xylene] : log Kow = 3.12 (measured) (ortho), 3.2 (measured) (meta), 3.15 (measurements) (p) (5)
- [Ethylbenzene] : log Kow = 3.15 (11)
- [Secret] : Koc = 1.838

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- High temperature incinerate
- After taking off organic solvents that are supposed to be recycled, incinerate the rest of them at a high degree.

B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

14. TRANSPORT INFORMATION

A. UN number

- 1263

B. Proper shipping name

- Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

C. Hazard class

- 3

D. Packing group

- II

E. Marine pollutant

- [Solvent naphtha (petroleum), light arom.] : Applicable
- [Ethylbenzene] : Applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

o POPs Management Law

- Not applicable

o Information of EU Classification

* Classification

- [Xylene] : R10 Xn; R20/21 Xi; R38
- [Propylene glycol methyl ether acetate] : R10
- [n-Butyl acetate] : R10 R66 R67
- [Solvent naphtha (petroleum), light arom.] : Carc. Cat. 2; R45/Muta. Cat. 2; R46, Xn; R65
- [Secret] : R10 Xi; R37
- [Ethylbenzene] : F; R11Xn; R20
- [Toluene] : F; R11 Repr.Cat.3; R63 Xn; R48/20-65 Xi; R38 R67
- [Secret] : Carc. Cat. 2; R45
- [Secret] : R10 R67
- [Secret] : R10 Xi; R37-41
- [Secret] : R10 Repr. Cat. 2; R61 Xi; R37
- [Secret] : Xi; R36
- [Secret] : R10 Repr. Cat. 2; R61 Xi; R37/38-41

* Risk Phrases

- [Xylene] : R10, R20/21, R38
- [Propylene glycol methyl ether acetate] : R10
- [n-Butyl acetate] : R10, R66, R67
- [Solvent naphtha (petroleum), light arom.] : R45, R65, R46
- [Secret] : R10, R37
- [Ethylbenzene] : R11, R20
- [Toluene] : R11, R38, R48/20, R63, R65, R67



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

- [Secret] : R45
- [Secret] : R10, R67
- [Secret] : R10, R37, R41
- [Secret] : R61, R10, R37
- [Secret] : R36
- [Secret] : R61, R10, R37/38, R41

*** Safety Phrase**

- [Xylene] : S2, S25
- [Propylene glycol methyl ether acetate] : S2
- [n-Butyl acetate] : S2, S25
- [Solvent naphtha (petroleum), light arom.] : S53, S45
- [Secret] : S2, S24
- [Ethylbenzene] : S2, S16, S24/25, S29
- [Toluene] : S2, S36/37, S46, S62
- [Secret] : S53, S45
- [Secret] : S2
- [Secret] : S2, S24, S26, S39
- [Secret] : S2, S24, S26

○ **U.S. Federal regulations**

*** OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

*** CERCLA Section 103 (40CFR302.4)**

- [Xylene] : 45.3599 kg 100 lb
- [n-Butyl acetate] : 2267.995 kg 5000 lb
- [Ethylbenzene] : 453.599 kg 1000 lb
- [Toluene] : 453.599 kg 1000 lb

*** EPCRA Section 302 (40CFR355.30)**

- Not applicable

*** EPCRA Section 304 (40CFR355.40)**

- Not applicable

*** EPCRA Section 313 (40CFR372.65)**

- [Xylene] : Applicable
- [Ethylbenzene] : Applicable
- [Toluene] : Applicable

○ **Rotterdam Convention listed ingredients**

- Not applicable

○ **Stockholm Convention listed ingredients**

- Not applicable

○ **Montreal Protocol listed ingredients**

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2013-06-26

C. Revision number and Last date revised

- Not applicable



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

D. Other

- This MSDS is prepared according to the Globally Harmonized System (GHS).



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.